

Low PIM Bulkhead Mount N Female to N Female Adapter



RF Adapters Technical Data Sheet

ET12476

Configuration

- N Female Connector 1
- N Female Connector 2
- 50 Ohm

- Low PIM Design
- Straight Body Geometry
- Bulkhead Mount Method

Features

- Max VSWR of 1.2:1 up to 6 GHz
- PIM levels lower than -160 dBc

Silver Plated Beryllium Copper Contact

Applications

- General Purpose Test
- Rack Mounted Equipment
- Low PIM Applications

Description

Ebeestock's ET12476 low PIM bulkhead type N female to type N female adapter is part of our full line of RF components available for same-day shipping. Our type N to type N adapter has a female to female gender configuration in a low PIM design. ET12476 type N female to type N female adapter operates to 6 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.2:1 maximum and passive intermodulation of -160 dBc maximum. This RF type N bulkhead to type N adapter allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.2:1	
Insertion Loss			0.1	dB
Passive Intermodulation			-160	dBc
using two 20W tones				

Electrical Specification Notes: Values at 25°C, sea level.

Mechanical Specifications

Size

Length 1.4 in [35.56 mm] Width 0.82 in [20.83 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Low PIM Bulkhead Mount N Female to N Female Adapter ET12476

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Low PIM Bulkhead Mount N Female to N Female Adapter



RF Adapters Technical Data Sheet

ET12476

Weight 0.11 lbs [49.9 g]

Description	Connector 1	Connector 2	
Туре	N Female	N Female	
Polarity	Standard	Standard	

Material Specifications

	Connector 1		Connector 2		
Description	Material	Plating	Material	Plating	
pe	N Female		N Female		
ntact	Beryllium Copper	Silver	Beryllium Copper	Silver	
sulation	PTFE		PTFE		
ıter Conductor	Brass	Tri-Metal	Brass	Tri-Metal	
ıter Conductor	Brass	Tri-Metal	Brass		

Environmental SpecificationsTemperature

Operating Range

-45 to +125 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Low PIM Bulkhead Mount N Female to N Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Low PIM Bulkhead Mount N Female to N Female Adapter ET12476

URL: https://www.ebeestock.com/low-pim-bulkhead-mount-n-female-to-n-female-adapter-0012476

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

ET12476 CAD Drawing
Low PIM Bulkhead Mount N Female to N Female Adapter

