

Hermetically Sealed N Female to N Female Bulkhead Mount Adap



RF Adapters Technical Data Sheet

ET1248

4

Configuration

- N Female Connector 1
- N Female Connector 2
- 50 Ohms

- Straight Body Geometry
- Bulkhead Mount Method

Features

- Max VSWR of 1.4:1 up to 3 GHz
- Hermetically Sealed
- N Interface compliant with MIL-STD-348A
- Gold Plated Brass Contact
- 30 µ-in min Gold Contact Plating

Applications

General Purpose Test

Vacuum Test Environment

Rack Mounted Equipment

Description

Ebeestock's ET12484 hermetically sealed type N to type N female bulkhead adapter is part of our full line of RF components available for same-day shipping. Our type N to type N adapter has a female to female gender configuration. ET12484 type N female to type N female adapter operates to 3 GHz. The Ebeestock RF adapter provides good VSWR of 1.4:1 maximum. This RF type N to type N bulkhead adapter allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. This hermetic type N to type N adapter prevents the leakage of gases, making it suitable for high pressure or vacuum applications or whenever an airtight seal is required.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications			
Erequency Range	DC	3	GHz
VSWR		1.4:1	
Operating Voltage (AC)		500	Vrms

Mechanical Specifications

Size

Length 1.539 in [39.09 mm] Width 0.866 in [22 mm] 0.116 lbs [52.62 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Hermetically Sealed N Female to N Female Bulkhead Adapter ET12484

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Hermetically Sealed N Female to N Female Bulkhead Mount Adap ter



RF Adapters Technical Data Sheet ET12484

Description	Connector 1	Connector 2
Type	N Female	N Female
Polarity	Standard	Standard
Interface Specification	MIL-STD-348A	MIL-STD-348A
Connector Option	Hermetically Sealed	Hermetically Sealed

Material Specifications

	Connector 1		Connector 2		
Description	Material	Plating	Material	Plating	
Туре	N Female		N Female		
Contact	Brass	Gold	Brass	Gold	
		30 µ-in minimum		30 µ-in minimum	
Insulation	PTFE		PTFE		
Outer Conductor	Brass	Nickel	Brass	Nickel	
		100 μ-in minimum		100 μ-in minimum	

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Hermetic Seal

Waterproof leak test pressure 7 kg/cm² min.

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Hermetically Sealed N Female to N Female Bulkhead Adapter ET12484

www.ebeestock.com



Hermetically Sealed N Female to N Female Bulkhead Mount Adap ter



RF Adapters Technical Data Sheet ET12484

Hermetically Sealed N Female to N Female Bulkhead Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Hermetically Sealed N Female to N Female Bulkhead Adapter ET12484

URL: https://www.ebeestock.com/hermetically-sealed-n-female-to-n-female-bulkhead-mount-adapter-0012484

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12484 CAD Drawing
Hermetically Sealed N Female to N Female Bulkhead Adapter

