

N Female to SC Male Adapter



# RF Adapters Technical Data Sheet

ET1249

9

## Configuration

- N Female Connector 1
- SC Male Connector 2

## Features

- Max VSWR of 1.25:1 up to 11 GHz
- Type N interface compliant with MIL-STD-348
- SC interface compliant with MIL-STD-348

- 50 Ohm
- Straight Body Geometry
- Contact plating according to QQ-S-365
- Silver Plated Beryllium Copper Contact

## Applications

Allows Connection Between Series
 General Purpose Test

#### Description

Ebeestock's ET12499 type N female to SC male adapter is part of our full line of RF components available for same-day shipping. Our type N to SC adapter has a female to male gender configuration. ET12499 type N female to SC male adapter operates to 11 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.25:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications			
Frequency Range	DC	11	GHz
VSWR		1.25:1	

Electrical Specification Notes: Values at 25°C, sea level.

### Mechanical Specifications

Size

Length
Width
0.79 in [20.07 mm]
Weight
0.1128 lbs [51.17 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female to SC Male Adapter ET12499

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



N Female to SC Male Adapter



# RF Adapters Technical Data Sheet ET12499

Connector 1	Connector 2	
N Female	SC Male	
Standard	ard	
MIL-STD-348	MIL-STD-348	
	N Female Standard	

## Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	N Female		SC Male	
Contact	Beryllium Copper	Silver	Beryllium Copper	Silver
		QQ-S-365		QQ-S-365
Insulation	PTFE		PTFE	
Outer Conductor	Brass	Nickel		
		QQ-N-290		
Body			Brass	Nickel
				QQ-N-290
Coupling Nut			Brass	Nickel
				QQ-N-290

## **Environmental Specifications**

Temperature

Operating Range -65 to +165 °C

Compliance Certifications (see product page for current document)

### Plotted and Other Data

Notes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female to SC Male Adapter ET12499



N Female to SC Male Adapter



# RF Adapters Technical Data Sheet ET12499

N Female to SC Male Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female to SC Male Adapter ET12499

URL: https://www.ebeestock.com/n-female-to-sc-male-adapter-0012499

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

