

N Female to N Female Right Angle Adapter



RF Adapters Technical Data Sheet

ET1251

Configuration

- N Female Connector 1
- N Female Connector 2

Features

- N Interface compliant with MIL-STD-348
- Silver Plated Contact

Applications

General Purpose Test

- 50 Ohms
- Right Angle Body Geometry

Contact Plating per QQ-S-365

Description

Ebeestock's ET12515 type N female to type N female right angle adapter is part of our full line of RF components available for same-day shipping. Our type N to type N adapter has a female to female gender configuration. This low profile right angle type N adapter allows for easier connections in tight spaces.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/ disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size					
Length	1.215 in [30.86 mm] 0.625 in [15.88 mm] 1.215 in [30.86 mm]				
Width					
Height					
Weight	0.118 lbs [53.52 g]				
Type	N Female	N Female			
Polarity	Standard	Standard			
Interface Specification	MIL-STD-348	MIL-STD-348			

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female to N Female Right Angle Adapter ET12515



N Female to N Female Right Angle Adapter



RF Adapters Technical Data Sheet ET12515

Material Specifications

Conne		ector 1	Conne	Connector 2	
Description	Material	Plating	Material	Plating	
Туре	N Female		N Female		
Contact		Silver		Silver	
		QQ-S-365		QQ-S-365	
Insulation	PTFE		PTFE		
Outer Conductor	Brass	Nickel	Brass	Nickel	
		QQ-N-290		QQ-N-290	

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

N Female to N Female Right Angle Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female to N Female Right Angle Adapter ET12515

URL: https://www.ebeestock.com/n-female-to-n-female-right-angle-adapter-0012515

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12515 CAD Drawing
N Female to N Female Right Angle Adapter

