

75 Ohm N Male to 75 Ohm N Female Adapter



RF Adapters Technical Data Sheet

ET1252

Configuration

- N Male Connector 1
- N Female Connector 2

- 75 Ohms
- Straight Body Geometry

Features

Gold Plated Brass Contact

• 50 μ-in min Gold Contact Plating

Applications

Connector Saver

General Purpose Test

Description

Ebeestock's ET12520 75 ohm type N male to type N female adapter is part of our full line of RF components available for same-day shipping. ET12520 type N male to type N female adapter operates to 1.5 GHz. The ET12520 Ebeestock RF adapter can also be used as a connector saver to extend equipment life.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications						
Erequency Range	DC	1.5	GHz			
Operating Voltage (AC)		1,000	Vrms			
Dielectric Withstanding Voltage (AC)		2,500	Vrms			

Mechanical Specifications

Size						
Length	1.39 in [35.31 r	1.39 in [35.31 mm]				
Width	0.83 in [21.08 mm]					
Weight	0.116 lbs [52.62 g]					
Туре	N Male	N Female				
Polarity	Standard	Standard				

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm N Male to N Female Adapter ET12520

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



75 Ohm N Male to 75 Ohm N Female Adapter



RF Adapters Technical Data Sheet ET12520

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	N Male		N Female	
Contact	Brass	Gold	Brass	Gold
		50 μ-in minimum		50 μ-in minimum
Insulation	PTFE		PTFE	
Outer Conductor			Brass	Nickel
				100 μ-in minimum
Body	Brass	Nickel		
		100 μ-in minimum		
Gasket	Silicone			
Coupling Nut	Brass	Nickel		
		100 μ-in minimum		

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

75 Ohm N Male to N Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm N Male to N Female Adapter ET12520

URL: https://www.ebeestock.com/75-ohm-n-male-to-75-ohm-n-female-adapter-0012520

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12520 CAD Drawing 75 Ohm N Male to N Female Adapter

