

SMA Female to N Female 4 Hole Flange Mount Adapter



RF Adapters Technical Data Sheet

ET1256

3

Configuration

- SMA Female Connector 1
- N Female Connector 2
- 50 Ohms

- Straight Body Geometry
- 4 Hole Flange Mount Method

Features

- Max VSWR of 1.3:1 up to 11 GHz
- SMA interface compliant with MIL-STD-348A
- N interface compliant with MIL-STD-348A
- 30 µ-in minimum contact plating
- Gold Plated Beryllium Copper Contact

Applications

- Allows Connection Between Series
- General Purpose Test
- Rack Mounted Equipment

Description

Ebeestock's ET12563 SMA female to type N female 4 hole flange mount adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to type N adapter has a female to female gender configuration. ET12563 SMA female to type N female adapter operates to 11 GHz. The Ebeestock RF adapter provides good VSWR of 1.3:1 maximum. This RF SMA to type N 4 hole flange adapter allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

lectrical Specifications			
Erequency Range	DC	11	GHz
VSWR		1.3:1	
Operating Voltage (AC)		500	Vrms
Dielectric Withstanding Voltage (AC)		1,000	Vrms

Mechanical Specifications

Size

Length Uidth 1.234 in [31.34 mm] 1 in [25.4 mm] 0.078 lbs [35.38 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to N Female 4 Hole Flange Mount Adapter ET12563

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Female to N Female 4 Hole Flange Mount Adapter



RF Adapters Technical Data Sheet ET12563

Description	Connector 1	Connector 2
Туре	SMA Female	N Female
Polarity	Standard	Standard
Interface Specification	MIL-STD-348A	MIL-STD-348A

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	SMA Female		N Female	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
		30 µ-in minimum		30 µ-in minimum
Insulation	PTFE		PTFE	
Outer Conductor	Brass	Nickel	Brass	Nickel
		100 μ-in minimum		100 μ-in minimum

Environmental SpecificationsTemperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to N Female 4 Hole Flange Mount Adapter ET12563



SMA Female to N Female 4 Hole Flange Mount Adapter



RF Adapters Technical Data Sheet ET12563

SMA Female to N Female 4 Hole Flange Mount Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to N Female 4 Hole Flange Mount Adapter ET12563

URL: https://www.ebeestock.com/sma-female-to-n-female-4-hole-flange-mount-adapter-0012563

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12563 CAD Drawing
SMA Female to N Female 4 Hole Flange Mount Adapter

