

Precision SMA Female to N Female Bulkhead Mount Adapter



RF Adapters Technical Data Sheet

ET1258

Configuration

- SMA Female Connector 1
- N Female Connector 2
- 50 Ohm

Features

- Max VSWR of 1.15:1 up to 18 GHz
- SMA interface compliant with MIL-STD-348
- Type N interface compliant with MIL-STD-348
- Gold Plated Beryllium Copper Contact

- Precision Design
- Straight Body Geometry
- Bulkhead Mount Method
- Max VSWR of 1.15:1 up to 18 GHz
- SMA Interface compliant with MIL-STD-348
- N Interface compliant with MIL-STD-348
- Gold Plated Beryllium Copper Contact

Applications

- Allows Connection Between Series
- General Purpose Test
- Rack Mounted Equipment
- Precision Test & Measurement
- Allows Connection Between Series
- General Purpose Test
- Rack Mounted Equipment
- Precision Test & Measurement

Description

Ebeestock's ET12580 SMA female to type N female bulkhead adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to type N adapter has a female to female gender configuration in a precision design. ET12580 SMA female to type N female adapter operates to 18 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.15:1 maximum. This RF SMA to type N bulkhead adapter allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

ctrical Specifications			
Frequency Range	DC	18	GHz
VSWR		1.15:1	
Operating Voltage (DC)		35	Vdc

Mechanical Specifications

Size

Length 1.5 in [38.1 mm] Width 1.071 in [27.2 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to N Female Bulkhead Mount Adapter ET12580

www.ebeestock.com

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Precision SMA Female to N Female Bulkhead Mount Adapter



RF Adapters Technical Data Sheet ET12580

Weight 0.09 lbs [40.82 g]

Description	Connector 1	Connector 2	
Type	SMA Female	N Female	
Polarity	Standard	Standard	
Interface Specification	MIL-STD-348	MIL-STD-348	

Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Туре	SMA Female		N Female	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
Outer Conductor P	assivated Stainless Steel		Passivated Stainless Steel	

Environmental SpecificationsTemperature

Operating Range -65 to +125 °C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Precision SMA Female to N Female Bulkhead Mount Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to N Female Bulkhead Mount Adapter ET12580

URL: https://www.ebeestock.com/precision-sma-female-to-n-female-bulkhead-mount-adapter-0012580

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

ET12580 CAD Drawing
Precision SMA Female to N Female Bulkhead Mount Adapter

