



RF Adapters Technical Data Sheet

ET1258

Configuration

- SMA Male Reverse Polarity Connector 1
- N Female Connector 2

- Max VSWR of 1.25:1 up to 11 GHz
- SMA Interface compliant with MIL-STD-348
- N Interface compliant with MIL-STD-348

- 50 Ohms
- Straight Body Geometry
- Gold Plated Brass Contact
- Contact Plating per MIL-G-45204

Applications

Features

 Allows Connection Between Series General Purpose Test

Description

Ebeestock's ET12588 reverse polarity SMA male to type N female adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our reverse polarity SMA to type N adapter has a male to female gender configuration. ET12588 reverse polarity SMA male to type N female adapter operates to 11 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.25:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/ disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Frequency Range	DC	11	GHz
VSWR		1.25:1	

Electrical Specification Notes: Values at 25°C, sea level

Mechanical Specifications

Size

1.27 in [32.26 mm] Length 0.69 in [17.53 mm] Width Weight 0.068 lbs [30.84 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price,









RF Adapters Technical Data Sheet ET12588

Description	Connector 1	Connector 2
Туре	SMA Male	N Female
Polarity	Reverse Polarity	Standard
Interface Specification	MIL-STD-348	MIL-STD-348
Hex Size	5/16 in.	
Mating Torque	3 to 5 in-lbs [0.34 to 0.57 Nm]	

Material Specifications

	Connector 1		Conn	ector 2
Description	on Material	Plating	Material	Plating
Туре	SMA Male Reverse Polarity		N Female	
Contact	Brass	Gold	Brass	Gold
		MIL-G-45204		MIL-G-45204
Insulation	PTFE		PTFE	
Outer Conducte	or		Brass	Nickel
				QQ-N-290
Body	Brass	Nickel		
		QQ-N-290		
Coupling Nut	Brass	Nickel		
		QQ-N-290		

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Reverse Polarity SMA Male to N Female Adapter ET12588





RF Adapters Technical Data Sheet ET12588

Reverse Polarity SMA Male to N Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Reverse Polarity SMA Male to N Female Adapter ET12588

URL: https://www.ebeestock.com/rp-sma-male-to-n-female-adapter-0012588

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12588 CAD Drawing
Reverse Polarity SMA Male to N Female Adapter

