

2.4mm NMD Female to N Female Adapter



RF Adapters Technical Data Sheet

ET1259

Configuration

- 2.4mm NMD Female Connector 1
- N Female Connector 2

Features

- Max VSWR of 1.15:1 up to 18 GHz
- 4 µin minimum contact plating

- 50 Ohm
- Straight Body Geometry
- Gold Plated Beryllium Copper Contact
- 30 µin min Gold Contact Plating

Applications

• Allows Connection Between Series

General Purpose Test

Description

Ebeestock's ET12590 2.4mm NMD female to type N female adapter is part of our full line of RF components available for same-day shipping. Our 2.4mm NMD to type N adapter has a female to female gender configuration built of durable stainless steel. ET12590 2.4mm NMD female to type N female adapter operates to 18 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.15:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

lectrical Specifications			
Erequency Range	DC	18	GHz
VSWR		1.15:1	
Operating Voltage (AC)		500	Vrms

Mechanical Specifications

Size
Lonath

Length	1.79 in [45.47 mm]	
Width	0.75 in [19.05 mm]	
Height	0.75 in [19.05 mm]	
Type	2.4mm NMD Female	N Female

Туре	2.4mm NMD Female	N Female
Polarity	Standard	Standard

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm NMD Female to N Female Adapter ET12590

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



2.4mm NMD Female to N Female Adapter



RF Adapters Technical Data Sheet ET12590

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	2.4mm NMD Female		N Female	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
		4 µin minimum		4 µin minimum
Body	Stainless Steel	Passivated Stainless Steel	Stainless Steel	Passivated Stainless Steel
		100 μin minimum		100 μin minimum

Environmental Specifications Temperature

Operating Range

-65 to +165 °C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

2.4mm NMD Female to N Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm NMD Female to N Female Adapter ET12590

URL: https://www.ebeestock.com/2-4mm-nmd-female-to-n-female-adapter-0012590

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

www.ebeestock.com

