

SC Male to SC Male Adapter



RF Adapters Technical Data Sheet

ET1260

6

Configuration

- SC Male Connector 1
- SC Male Connector 2

• 50 Ohms

Straight Body Geometry

Features

- SC Interface compliant with MIL-STD-348
- Silver Plated Brass Contact

Applications

General Purpose Test

Contact Plating per QQ-S-365

Description

Ebeestock's ET12606 SC male to SC male adapter is part of our full line of RF components available for same-day shipping. Our SC to SC adapter has a male to male gender configuration.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size					
Length	1.7 in [43.18	1.7 in [43.18 mm]			
Width	0.78 in [19.81 mm]				
Weight	0.137 lbs [6	0.137 lbs [62.14 g]			
Type	SC Male	SC Male			
Polarity	Standard	Standard			
Interface Specification	MIL-STD-348	MIL-STD-348			

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SC Male to SC Male Adapter ET12606



SC Male to SC Male Adapter



RF Adapters Technical Data Sheet ET12606

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	SC Male		SC Male	
Contact	Brass	Silver	Brass	Silver
		QQ-S-365		QQ-S-365
Insulation	PTFE		PTFE	
Body	Brass	Nickel	Brass	Nickel
		QQ-N-290		QQ-N-290
Coupling Nut	Brass	Nickel	Brass	Nickel
		QQ-N-290		QQ-N-290

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SC Male to SC Male Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SC Male to SC Male Adapter ET12606

URL: https://www.ebeestock.com/sc-male-to-sc-male-adapter-0012606

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

