

SMA Male to UMCX Jack Adapter



RF Adapters Technical Data Sheet

ET12626

Configuration

- SMA Male Connector 1
- UMCX Jack Connector 2

- 50 Ohms
- Straight Body Geometry

Features

- Max VSWR of 1.3:1 up to 6 GHz
- SMA interface compliant with MIL-STD-348A
- 50 µin minimum contact plating
- Gold Plated Brass Contact

Applications

Allows Connection Between Series

General Purpose Test

Description

Ebeestock's ET12626 SMA male to UMCX jack adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to UMCX adapter has a male to jack gender configuration. ET12626 SMA male to UMCX jack adapter is gold plated and operates to 6 GHz. The Ebeestock RF adapter provides good VSWR of 1.3:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC	OC 6 GHz		
VSWR	1.3:1			
Operating Voltage (AC)			100	Vrms

Electrical Specification Notes: Values at 25° sea level.

Mechanical Specifications

Size

Length Width Weight

0.415 in [10.54 mm] 0.315 in [8 mm] 0.006 lbs [2.72 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to UMCX Jack Adapter ET12626

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Male to UMCX Jack Adapter



RF Adapters Technical Data Sheet

ET12626

Description	Connector 1	Connector 2	
Type	SMA Male	UMCX Jack	
Polarity	Standard	Standard	
Interface Specification	MIL-STD-348A		
Hex Size	5/16 inch		
Mating Torque	3 to 5 in-lbs [0.34 to 0.57 Nm]		

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	SMA Male		UMCX Jack	
Contact	Brass	Gold	Brass	Gold
		50 µin minimum		50 µin minimum
Insulation	PTFE		PTFE	
Outer Conductor			Brass	Gold
				3 µin minimum
Body	Brass	Gold		
		3 µin minimum		

Environmental SpecificationsTemperature

Operating Range

-40 to +90 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to UMCX Jack Adapter ET12626



SMA Male to UMCX Jack Adapter



RF Adapters Technical Data Sheet

ET12626

SMA Male to UMCX Jack Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to UMCX Jack Adapter ET12626

URL: https://www.ebeestock.com/sma-male-to-umcx-jack-adapter-0012626

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12626 CAD Drawing SMA Male to UMCX Jack Adapter

