

Precision SMA Female to SMP Male Limited Detent 2 Hole Flang e Mount Adapter



RF Adapters Technical Data Sheet

ET12638

Configuration

- SMA Female Connector 1
- Limited Detent SMP Male Connector 2
- 50 Ohms

- Precision Design
- Straight Body Geometry
- 2 Hole Flange Mount Method

Features

- Max VSWR of 1.2:1 up to 26.5 GHz
- SMA Interface compliant with MIL-STD-348
- SMP Interface compliant with MIL-STD-348
- Gold Plated Beryllium Copper Contact
- Contact Plating per MIL-G-45204

Applications

- Allows Connection Between Series
- General Purpose Test
- Rack Mounted Equipment
- Precision Test & Measurement

Description

Ebeestock's ET12638 precision SMA female to SMP male limited detent 2 hole flange adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to SMP adapter has a female to male gender configuration in a precision design. ET12638 SMA female to SMP male adapter operates to 26.5 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.2:1 maximum. This RF SMA to SMP 2 hole flange adapter allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		26.5	GHz
VSWR			1.2:1	

Electrical Specification Notes: Values at 25°C, sea level.

Mechanical Specifications

 Size

 Length
 0.78 in [19.81 mm]

 Width
 0.625 in [15.88 mm]

 Height
 0.281 in [7.14 mm]

 Weight
 0.0103 lbs [4.67 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to SMP Male Limited Detent 2 Hole Flange Adapter ET12638

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Precision SMA Female to SMP Male Limited Detent 2 Hole Flang e Mount Adapter



RF Adapters Technical Data Sheet

ET12638

Description	Connector 1	Connector 2
Туре	SMA Female	SMP Male
Polarity	Standard	Standard
Interface Specification	MIL-STD-348	MIL-STD-348
Mating Cycles	500	500

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	SMA Female		Limited Detent SMP Male	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
		MIL-G-45204		MIL-G-45204
Insulation	PTFE		PTFE	
Outer Conductor Pa	assivated Stainless Steel			
		AMS-QQ-P-35		
Body			Passivated Stainless Steel	
				AMS-QQ-P-35

Environmental Specifications

Temperature

Operating Range

-55 to +125 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to SMP Male Limited Detent 2 Hole Flange Adapter ET12638



Precision SMA Female to SMP Male Limited Detent 2 Hole Flang e Mount Adapter



RF Adapters Technical Data Sheet

ET12638

Precision SMA Female to SMP Male Limited Detent 2 Hole Flange Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to SMP Male Limited Detent 2 Hole Flange Adapter ET12638

URL: https://www.ebeestock.com/precision-sma-female-to-smp-male-limited-detent-2-hole-flange-mo unt-adapter-0012638

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12638 CAD Drawing
Precision SMA Female to SMP Male Limited Detent 2 Hole Flange Adapter

