

Precision SMA Female to ZMA Jack Adapter, 3 Lug



RF Adapters Technical Data Sheet

ET12639

Configuration

- SMA Female Connector 1
- ZMA Jack Connector 2
- 50 Ohms

- Precision Design
- Straight Body Geometry

Features

- Max VSWR of 1.15:1 up to 18 GHz
- Gold over Nickel Plated Beryllium Copper Contact
- Contact Plating per MIL-G-45204

Applications

- Allows Connection Between Series
- General Purpose Test
- Precision Test & Measurement

Description

Ebeestock's ET12639 precision SMA female to ZMA jack adapter is part of our full line of RF components available for sameday shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to ZMA adapter has a female to jack gender configuration in a precision design. ET12639 SMA female to ZMA jack adapter operates to 18 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.15:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.15:1	
Insertion Loss			0.22	dB

Electrical Specification Notes: Values at 25°C, sea level. Insertion Loss (dB) = 0.05*sqrt(fGHz).

Mechanical Specifications

Size

Length 0.814 in [20.68 mm] Weight 0.001 lbs [0.45 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to ZMA Jack Adapter 3 Lug ET12639

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Precision SMA Female to ZMA Jack Adapter, 3 Lug



RF Adapters Technical Data Sheet

ET12639

Description	Connector 1	Connector 2
Туре	SMA Female	ZMA Jack
Polarity	Standard	Standard
Mating Cycles	500	500

Material Specifications

	Connector 1		Connector 2		
Description	Material	Plating	Material	Plating	
Туре	SMA Female		ZMA Jack		
Contact	Beryllium Copper	Gold over Nickel	Beryllium Copper	Gold over Nickel	
		MIL-G-45204		MIL-G-45204	
Insulation	PTFE		PTFE		
Outer Conductor Pa	assivated Stainless Steel		Passivated Stainless Steel		
		ASTM A380		ASTM A380	

Environmental Specifications

Temperature

Operating Range -55 to +100 deg C

Vibration WIL-STD-202, Method 204, Cond. D (20G's)

Salt Spray MIL-STD-202, Method 101, Cond. B, 5% salt solution

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to ZMA Jack Adapter 3 Lug ET12639



Precision SMA Female to ZMA Jack Adapter, 3 Lug



RF Adapters Technical Data Sheet

ET12639

Precision SMA Female to ZMA Jack Adapter 3 Lug from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to ZMA Jack Adapter 3 Lug ET12639

URL: https://www.ebeestock.com/precision-sma-female-to-zma-jack-adapter-3-lug-0012639

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12639 CAD Drawing
Precision SMA Female to ZMA Jack Adapter 3 Lug

