



RF Adapters Technical Data Sheet

ET1270

1

Configuration

- SMA Female Connector 1
- SMA Female Connector 2
- 50 Ohms

- Straight Body Geometry
- Bulkhead Mount Method

Features

- Max VSWR of 1.4:1 up to 18 GHz
- Hermetically Sealed
- SMA Interface compliant with MIL-STD-348
- Gold Plated Beryllium Copper Contact
- Contact Plating per MIL-G-45204

Applications

General Purpose Test

Vacuum Test Environment

Rack Mounted Equipment

Description

Ebeestock's ET12701 hermetically sealed SMA female to SMA female bulkhead adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm

(K) connectors. Our SMA to SMA adapter has a female to female gender configuration. ET12701 SMA female to SMA female adapter operates to 18 GHz. The Ebeestock RF adapter provides good VSWR of 1.4:1 maximum. This RF SMA to SMA bulkhead adapter allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. This hermetic SMA to SMA adapter prevents the leakage of gases, making it suitable for high pressure or vacuum applications or whenever an airtight seal is required.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Frequency Range	DC	18	GHz
VSWR		1.4:1	

Electrical Specification Notes: Values at 25°C, sea level.

Mechanical Specifications

Size

 Length
 0.875 in [22.23 mm]

 Width
 0.5 in [12.7 mm]

 Weight
 0.013 lbs [5.9 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price,

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.





ılk





RF Adapters Technical Data Sheet ET12701

Description	Connector 1	Connector 2
Туре	SMA Female	SMA Female
Polarity	Standard	Standard
Interface Specification	MIL-STD-348	MIL-STD-348
Connector Option	Hermetically Sealed	Hermetically Sealed

Material Specifications

	Connector 1		Conne	ctor 2
Description	Material	Plating	Material	Plating
Туре	SMA Female		SMA Female	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
		MIL-G-45204		MIL-G-45204
Insulation	PTFE		PTFE	
Outer Conductor	Stainless Steel	Gold	Stainless Steel	Gold
		MIL-G-45204		MIL-G-45204

Environmental Specifications

Temperature

Operating Range -65 to +165 deg C

Hermetic Seal

Leak rate not to exceed 1x10^-7 cc/sec of helium at 1

atm differential.

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Hermetically Sealed SMA Female to SMA Female Bulkhead Adapter ET12701





RF Adapters Technical Data Sheet ET12701

Hermetically Sealed SMA Female to SMA Female Bulkhead Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Hermetically Sealed SMA Female to SMA Female Bulkhead Adapter ET12701

URL: https://www.ebeestock.com/hermetically-sealed-sma-female-to-sma-female-bulkhead-mount-adap ter-0012701

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12701 CAD Drawing
Hermetically Sealed SMA Female to SMA Female Bulkhead Adapter

