

SMA Female to TNC Female Adapter



RF Adapters Technical Data Sheet

ET1272

1

Configuration

- SMA Female Connector 1
- TNC Female Connector 2

Features

- Max VSWR of 1.25:1 up to 18 GHz
- SMA interface compliant with MIL-C-39012
- TNC interface compliant with MIL-C-39012
- Gold Plated Beryllium Copper Contact

- 50 Ohm
- Straight Body Geometry
- Max VSWR of 1.25:1 up to 18 GHz
- SMA Interface compliant with MIL-C-39012
- TNC Interface compliant with MIL-C-39012
- Gold Plated Beryllium Copper Contact

Applications

- Allows Connection Between Series
- General Purpose Test
- Allows Connection Between Series
- General Purpose Test

Description

Ebeestock's ET12721 SMA female to TNC female adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to TNC adapter has a female to female gender configuration. ET12721 SMA female to TNC female adapter operates to 18 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.25:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications			
Frequency Range	DC	18	GHz
VSWR		1.25:1	

Mechanical Specifications

Size
Length
Width
Weight

1.62 in [41.15 mm] 0.56 in [14.22 mm] 0.0602 lbs [27.31 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to TNC Female Adapter ET12721

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Female to TNC Female Adapter



RF Adapters Technical Data Sheet ET12721

TNC Female
Standard
MIL-C-39012
-

Mechanical Specification Notes: TNC connector is mode free up to 18 GHz.

Material Specifications

Description	Connector 1		Connector 2		
	Material	Plating	Material	Plating	
Туре	SMA Female		TNC Female		
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold	
Outer Conductor Pa	assivated Stainless Steel		Passivated Stainless Steel		

Environmental Specifications

Temperature

Operating Range

-65 to +125 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to TNC Female Adapter ET12721



SMA Female to TNC Female Adapter



RF Adapters Technical Data Sheet ET12721

SMA Female to TNC Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to TNC Female Adapter ET12721

URL: https://www.ebeestock.com/sma-female-to-tnc-female-adapter-0012721

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

