

Precision TNC Male to TNC Female Adapter



RF Adapters Technical Data Sheet

ET12829

Configuration

- TNC Male Connector 1
- TNC Female Connector 2
- 50 Ohm

- Precision Design
- Straight Body Geometry

Features

• Max VSWR of 1.15:1 up to 18 GHz

Gold over Nickel Plated Beryllium Copper Contact

Applications

Connector Saver

- General Purpose Test
- Precision Test & Measurement

Description

Ebeestock's ET12829 TNC male to TNC female adapter is part of our full line of RF components available for same-day shipping. Our TNC to TNC adapter has a male to female gender configuration in a precision design. ET12829 TNC male to TNC female adapter operates to 18 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.15:1 maximum. The ET12829 Ebeestock RF adapter can also be used as a connector saver to extend equipment life.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR		1.15:1		
Insertion Loss			0.22	dB

Electrical Specification Notes: Values at 25°C, sea level. Insertion Loss (dB) = 0.05*sqrt(fGHz).

Mechanical Specifications

Size

Length 1.031 in [26.19 mm] Width 0.625 in [15.88 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision TNC Male to TNC Female Adapter ET12829

www.ebeestock.com

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Precision TNC Male to TNC Female Adapter



RF Adapters Technical Data Sheet

ET12829

Description	Connector 1	Connector 2
Туре	TNC Male	TNC Female
Polarity	Standard	Standard
Mating Cycles	500	
Hex Size	9/16 in.	

Material Specifications

	Connector 1		Connector 2		
Description	n Material	Plating	Material	Plating	
Туре	TNC Male		TNC Female		
Contact	Beryllium Copper	Gold over Nickel	Beryllium Copper	Gold over Nickel	
Insulation	PTFE		PTFE		
Outer Conductor			Passivated Stainless Steel		
Body	Passivated Stainless Steel				
Gasket	Silicone Rubber				
Coupling Nut	Passivated Stainless Steel				

Environmental Specifications

Temperature

Operating Range -65 to +165 °C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision TNC Male to TNC Female Adapter ET12829

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Precision TNC Male to TNC Female Adapter



RF Adapters Technical Data Sheet

ET12829

Precision TNC Male to TNC Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision TNC Male to TNC Female Adapter ET12829

URL: https://www.ebeestock.com/precision-tnc-male-to-tnc-female-adapter-0012829

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

