



RF Adapters Technical Data Sheet

ET1283

Configuration

- TNC Female Connector 1
- TNC Female Connector 2
- 50 Ohm

- Straight Body Geometry
- Bulkhead Mount Method

Features

- Max VSWR of 1.3:1 up to 6 GHz
- Hermetically Sealed
- TNC interface compliant with MIL-STD-348
- Contact plating according to MIL-G-45204
- Gold Plated Brass Contact

Applications

General Purpose Test

Vacuum Test Environment

Rack Mounted Equipment

Description

Ebeestock's ET12830 hermetically sealed TNC female to TNC female bulkhead adapter is part of our full line of RF components available for same-day shipping. Our TNC to TNC adapter has a female to female gender configuration. ET12830 TNC female to TNC female adapter operates to 6 GHz. The Ebeestock RF adapter provides good VSWR of 1.3:1 maximum. This RF TNC to TNC bulkhead adapter allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. This hermetic TNC to TNC adapter prevents the leakage of gases, making it suitable for high pressure or vacuum applications or whenever an airtight seal is required.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications			
Frequency Range	DC	6	GHz
VSWR		1.3:1	
Operating Voltage (AC)		500	Vrms

Mechanical Specifications

Size	
Length	1.555 in [39.5 mm]
Width	0.689 in [17.5 mm]
Height	0.689 in [17.5 mm]
Weight	0.052 lbs [23.59 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price,

www.ebeestock.com

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



lkł







RF Adapters Technical Data Sheet ET12830

Description	Connector 1	Connector 2
Туре	TNC Female	TNC Female
Polarity	Standard	Standard
Interface Specification	MIL-STD-348	MIL-STD-348
Connector Option	Hermetically Sealed	Hermetically Sealed

Material Specifications

	Connector 1		Conne	ector 2
Description	Material	Plating	Material	Plating
Туре	TNC Female		TNC Female	
Contact	Brass	Gold	Brass	Gold
		MIL-G-45204		MIL-G-45204
Insulation	PTFE		PTFE	
Outer Conductor	Brass	Nickel	Brass	Nickel
		QQ-N-290		QQ-N-290

Environmental Specifications

Temperature

Operating Range -65 to +165 deg C

Humidity IP 67 Rated

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Hermetically Sealed TNC Female to TNC Female Bulkhead Mount Adapter ET12830





RF Adapters Technical Data Sheet ET12830

Hermetically Sealed TNC Female to TNC Female Bulkhead Mount Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Hermetically Sealed TNC Female to TNC Female Bulkhead Mount Adapter ET12830

URL: https://www.ebeestock.com/hermetically-sealed-tnc-female-to-tnc-female-bulkhead-mount-adap ter-0012830

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12830 CAD Drawing
Hermetically Sealed TNC Female to TNC Female Bulkhead Mount Adapter

