

TNC Male to TNC Male Right Angle Adapter



RF Adapters Technical Data Sheet

ET1284

2

Configuration

- TNC Male Connector 1
- TNC Male Connector 2

- 50 Ohms
- Right Angle Body Geometry

Features

- TNC Interface compliant with MIL-STD-348
- Silver Plated Contact

Applications

General Purpose Test

Contact Plating per QQ-S-365

Description

Ebeestock's ET12842 TNC male to TNC male right angle adapter is part of our full line of RF components available for same- day shipping. Our TNC to TNC adapter has a male to male gender configuration. This low profile right angle TNC adapter allows for easier connections in tight spaces.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size					
Length	1.03 in [26.	16 mm]			
Width	0.59 in [14.99 mm] 1.03 in [26.16 mm]				
Height					
Weight	0.075 lbs [34.02 g]				
Type	TNC Male	TNC Male			
Polarity	Standard	Standard			
Interface Specification	MIL-STD-348	MIL-STD-348			

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Male to TNC Male Right Angle Adapter ET12842



TNC Male to TNC Male Right Angle Adapter



RF Adapters Technical Data Sheet ET12842

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	TNC Male		TNC Male	
Contact		Silver		Silver
		QQ-S-365		QQ-S-365
Insulation	PTFE		PTFE	
Body	Brass	Nickel	Brass	Nickel
		QQ-N-290		QQ-N-290
Coupling Nut	Brass	Nickel	Brass	Nickel
		QQ-N-290		QQ-N-290

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

TNC Male to TNC Male Right Angle Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Male to TNC Male Right Angle Adapter ET12842

URL: https://www.ebeestock.com/tnc-male-to-tnc-male-right-angle-adapter-0012842

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12842 CAD Drawing
TNC Male to TNC Male Right Angle Adapter

