



ble connector



Launch Pins Technical Data Sheet

ET12932

Configuration

• 50 Ohms

Applications

- General Purpose Test
- Rack and Panel Mount Applications
- Used in Field Replaceable
 Connectors
- Allows for Replacement of Damaged Connectors

Description

Ebeestock's ET12932 Launch pin & dielectric for 0.91mm (.036inch) field replaceable connector is part of our complete line of Connector Launch Accessories available for same-day shipping. This range of accessories includes Glass bead Transitions, Launch Pin & Dielectric Transitions and Pin/Tab Transitions to Microstrip and Stripline Circuits in conjunction with our line of field replaceable flange connectors. These accessories are designed to be compatible with our line of Field Replaceable Connectors to ensure optimal electrical performance for PCB test applications. They are available in commonly used pin diameters of .009", .012", .015", .018", .020"and .036" and in a variety of lengths and sizes depending on the application.

Our ET12932 Launch pin & dielectric for 0.91mm (.036inch) field replaceable connector datasheet specifications are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same day.

Mechanical Specifications

Dimensions

 Pin Length
 0.237 in [6.02 mm]

 Pin Diameter
 0.036 in [0.91 mm]

 Tab Length
 0.05 in [1.27 mm]

 Tab Diameter
 0.01 in [0.25 mm]

 Dielectric Length
 0.187 in [4.75 mm]

 Dielectric Diameter
 0.117 in [2.97 mm]

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Launch pin & dielectric for 0.91mm (.036inch) field replaceable connector ET12932





Launch pin & dielectric for 0.91mm (.036inch) field replacea

ble connector



Launch Pins Technical Data Sheet

ET12932

Launch pin & dielectric for 0.91mm (.036inch) field replaceable connector from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Launch pin & dielectric for 0.91mm (.036inch) field replaceable connector ET12932

URL: https://www.ebeestock.com/launch-pin-dielectric-for-0-91mm-036inch-field-replaceable-connector-0012932

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

