


| COMPONENTS  | IMPEDANCE |
|-------------|-----------|
| 1.85mm MALE | 50 OHM    |
| SMA MALE    | 50 OHM    |
| RG405/U     | 50 OHM    |

| Standard Lengths |                         |
|------------------|-------------------------|
| -12              | 12"                     |
| -24              | 24"                     |
| -36              | 36"                     |
| -48              | 48"                     |
| -60              | 60"                     |
| -XXX             | Custom Length in inches |



RoHS  
Compliance  
Certified


**8TH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN, 523900, DONGGUAN, GUANGDONG, CHINA**  
 WEBSITE: [www.ebeestock.com](http://www.ebeestock.com)  
 EMAIL: [sales@ebeestock.com](mailto:sales@ebeestock.com)

|                |                |   |                      |
|----------------|----------------|---|----------------------|
| <b>ET13422</b> |                | DES. CABLE ASSEMBLY, RG405/U, 1.85mm MALE TO SMA MALE (LEAD FREE) |                      |
| REV. A         | FSCM NO. 53919 | CAD FILE 021208   | SCALE N/A SIZE A 147 |

- NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
  2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
  3. DIMENSIONS ARE IN INCHES.
  4. LENGTH TOLERANCE IS  $\pm 1.5\%$  OR  $\pm 3/8"$ , WHICHEVER IS GREATER.