SMA Male to 1.85mm Male Cable 12 Inch Length Using Coax **REVISIONS** REV. DESCRIPTION DATE APPROVED Α **INITIAL RELEASE** 11/08/19 S.ELLIS LENGTH MEASURED FROM CONTACT TO CONTACT 5/16 HEX 2X TYP HEAT SHRINK SLEEVE CONTACT CONTACT **SMA MALE** 1.85mm MALE UNLESS OTHERWISE SPECIFIED THIRD-ANGLE PROJECTION **ebeestock** LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS (() TOLERANCES: THE INFORMATION AND $.X = \pm .2$ [5.08] FRACTIONS DESIGN IN THIS DOCUMENT .XX = ±.02 [.51] ± 1/32 8TH FLOOR, BUILDING 1. IS THE PROPERTY OF EBEESTOCK CORPORATION. $.XXX = \pm .005[.13]$ ANGLES ± 1° YONGFU SCIENCE AND TECHNOLOGY ALL RIGHTS RESERVED. CABLE LENGTH (L) TOLERANCES: CENTER INDUSTRIAL PARK, NANZHA DISTRICT SHEET L ≤ 12 [305] = +1 [25] / -0 5, HUMEN, 523900, DONGGUAN, GUANGDONG, CHINA 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 WEBSITE: www.ebeestock.com 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 SCALE EMAIL: sales@ebeestock.com N/A 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0

PART NUMBER

ÒV13440

REV

Α

SIZE CAGE CODE DRAWN BY

K.DANG

53919

ALL DIMENSIONS SHOWN

ARE FOR REFERENCE ONLY.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.