Plenum 4.1/9.5 Mini DIN Male Right Angle to N Male Low PIM Cable 200 cm Length Using SPP-250-LLPL Coax Using Times Microwave Parts REV. **DESCRIPTION** DATE APPROVED INITIAL RELEASE 04/09/19 S.ELLIS LENGTH MEASURED FROM CONTACT TO CONTACT **HEAT SHRINK** PIM LEVEL **PROTECTOR** -zzzdBc (2X) **PIM LABEL** SPP-250-LLPL 6" FROM CABLE END 1 PLACE. - LABEL CENTERED 84" OR LESS. CONTACT 22mm HEX 13/16 HEX -- GREATER THAN 84" LABEL 2 PLACES 12" FROM CABLE END. CONTACT N MALE 4.1/9.5 Mini **DIN MALE** RA UNLESS OTHERWISE SPECIFIED THE INFORMATION AND ebeestock DESIGN IN THIS DOCUMENT IS DIMENSIONS IN [] ARE MILLIMETERS THE PROPERTY OF EBEESTOCK CORPORATION. TOLERANCES: 8TH FLOOR, BUILDING 1, ALL RIGHTS RESERVED. .X=± .2 [5.08] FRACTIONS YONGFU SCIENCE AND TECHNOLOGY .XX=± .01 [.25] ± 1/32 SHEET CENTER INDUSTRIAL PARK, NANZHA DISTRICT XXX=± .005 [.13] ANGLES ± 1° 5, HUMEN, 523900, DONGGUAN, GUANGDONG, CHINA ALL DIMENSIONS SHOWN WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com SCALE ARE FOR REFERENCE ONLY. N/A THIRD-ANGLE PROJECTION

SIZE CAGE

53919

DRAWN BY

K.DANG

PART NUMBER

ET14093

REV

Α

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS, DIVERSION CONTRARY TO U.S. LAW PROHIBITED.