REVISIONS REV. DESCRIPTION DATE APPROVED А INITIAL RELEASE 04/07/2021 SELLIS В ADD PIM LABEL, UPDATE NOTES 8/3/21 LENGTH MEASURED FROM CONTACT TO CONTACT 2X SHRINK TUBE, TFT-402 BLACK PIM LABEL SERIAL # **PIM LEVEL** -zzzdBc (SEE NOTE 1 -2X 4.1/9.5 MINI DIN MALE (SEE NOTE 2) **B** UNLESS OTHERWISE SPECIFIED THIRD-ANGLE PROJECTION NOTES: ebeestock LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS - **(** TOLERANCES: 1. CABLES 84" AND UNDER HAVE 1 LABEL CENTERED. THE INFORMATION AND .X = ±.2 [5.08] FRACTIONS 8TH FLOOR, BUILDING 1, DESIGN IN THIS DOCUMENT .XX = ±.02 [.51] CABLES OVER 84" HAVE 2 LABELS, ONE AT EACH ± 1/32 IS THE PROPERTY OF YONGFU SCIENCE AND TECHNOLOGY .XXX = ±.005 [.13] ANGLES ± 1° EBEESTOCK CORPORATION END 12" FROM THE FRONT OF THE CONNECTOR. CENTER INDUSTRIAL PARK, NANZHA DISTRICT ALL RIGHTS RESERVED. CABLE LENGTH (L) TOLERANCES: 2. PIM LABEL 6" FROM CABLE END 1 PLACE. 5, HUMEN, 523900, DONGGUAN, GUANGDONG, CHINA SHEET OF L ≤ 12 [305] = +1 [25] / -0 1 1 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 WEBSITE: www.ebeestock.com 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 SCALE EMAIL: sales@ebeestock.com N/A 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0

300 [7620] < L = +5%L / -0

ALL DIMENSIONS SHOWN

ARE FOR REFERENCE ONLY

SIZE CAGE CODE DRAWN BY

53919 DFRISIELLO

А

ITEM NO.

ET14171

REV

В

4.1/9.5 Mini DIN Male to 4.1/9.5 Mini DIN Male Low PIM Cable 50 CM Length Using TFT-402 Coax Using Times Microwave Components

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.