REVISIONS REV. DESCRIPTION DATE APPROVED А INITIAL RELEASE 04/09/19 S.ELLIS LENGTH MEASURED FROM CONTACT TO CONTACT HEAT SHRINK **PIM LEVEL** PROTECTOR -zzzdBc (2X) PIM LABEL 6" FROM CABLE END 22mm HEX SPP-250-LLPL 1 PLACE. 13/16 HEX-LABEL CENTERED 84" OR LESS. - GREATER THAN 84" LABEL 2 PLACES CONTACT 12" FROM CABLE END. CONTACT 4.3-10 MALE N MALE RA RA UNLESS OTHERWISE SPECIFIED THE INFORMATION AND **ebeestock** LEADING DIMENSIONS ARE INCHES DESIGN IN THIS DOCUMENT IS * DIMENSIONS IN [] ARE MILLIMETERS THE PROPERTY OF EBEESTOCK CORPORATION. TOLERANCES: 8TH FLOOR, BUILDING 1. ALL RIGHTS RESERVED. .X=± .2 [5.08] FRACTIONS YONGFU SCIENCE AND TECHNOLOGY .XX=± .01 [.25] ± 1/32 SHEET OF CENTER INDUSTRIAL PARK, NANZHA DISTRICT XXX=± .005[.13] ANGLES ± 1° 1 1 5, HUMEN, 523900, DONGGUAN, GUANGDONG, CHINA ALL DIMENSIONS SHOWN WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com SCALE ARE FOR REFERENCE ONLY. N/A THIRD-ANGLE PROJECTION SIZE CAGE DRAWN BY PART NUMBER REV THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED. (-) 53919 А **K.DANG** ET14829 А

Plenum 4.3-10 Male Right Angle to N Male Right Angle Low PIM Cable 150 cm Length Using SPP-250-LLPL Coax Using Times Microwave Parts