COMPONENTS	IMPEDANCE		Standard Lengths					
7/16 MALE 7/16 MALE	50 OHM 50 OHM			-12	12"			
PE-SR401FL	50 OHM			-24	24"			
				-36	36"			
				-48	48"			
				-60	60"			
				-XXX	Custon	n Length ir	n inche	es
		LENGTH MEASURED	FROM					
		CONTACT TO CO						
						\bigcap		
		11		С				
1.250		((——[]	∇	$\left(\right)$		
		\longrightarrow)-		—Д,	$\Delta \parallel$			
				Ч				
						\square		
7/1 MA'	6				7/1 MAI			
14122	X					LE		
	~OC.'							
	estock		STH FLOOR, B				יחאטיטע	C V
	Nee Contraction		CENTER	RINDUSTR	IAL PARK, NA	ANZHA DISTRIC	T 5,	01
	- er				NGGUAN, GI E: www.ebees	UANGDONG, CH stock com	IINA	
			ebeestock		sales@ebees			
			DWG TITLE	DES.	CABLE ASSEN	IBLY, PE-SR401F	L. 7/16	
			ET16020			MALE (LEAD FRE		
		RoHS 2002/95/EC	REV. A FSCM NO. 53919	CAD FIL	E 020808	SCALE N/A	SIZE A	147
		RoHS	NOTES: 1. UNLESS OTHERWISE SPECIFIED		SIONS ARE N	OMINAL.		
		Compliance Certified	2. ALL SPECIFICATIONS ARE SUBJ 3. DIMENSIONS ARE IN INCHES.	ЕСТ ТО СН	ANGE WITHO	UT NOTICE AT A	NY TIME.	-
			4. LENGTH TOLERANCE IS ± 1.5% O	R ± 3/8", W	HICHEVER IS	GREATER.		