7/16 DIN MALE 50 OHM 7/16 DIN FEMALE 50 OHM 96 60° -72 72° 120°	COMPONENTS	IMPEDANCE				Standard Lengths				hs
T/16 DIN FEMALE B0 OHM PE-C195 50 OHM -48 48" -40 60" -72 72" -120 120" -xxx Custom Length in Inches -xxx -xxx -xxxx -xxx							-36	36"		
PE-C195 50 OHM -60 °° -72 72" -120 120" -XXX Custom Length in Inches -XXX Custom Length in							-48	48"		
-72 72" -120 '120" -200 '20" -200 Custom Length in Inches -20 '20" -200 Custom Length in Inches -20 '20" -200 Custom Length in Inches -20 '20' -200 Custom Length in Inches -20 '20' -20							-60	60"		
LENGTH MEASURED FROM CONTACT TO CONTACT 1.2500 1.2500 MALE M29 X 1.5-6G THELOOR, BUILDING 1, YONGTO SCIENCE AND TECHNOLOGY CENTER MUSTRAL DARK, MARTIA DETENDIOS UNDERSCHOOL OF MUST AND TECHNOLOGY							-72	72"		
LENGTH MEASURED FROM CONTACT TO CONTACT 1.250¢ 1.250¢ TIS DIN MALE TH FLORE. BUILDING 1, YUNDEU SCIENCE AND TECHNOLOGY CENTER BUILSTOR 1, YUNDEU SCIENCE AND TECHNOLOGY							-120	120"		
CONTACT TO CONTACT CONTACT TO CONTACT CONTAC							-XXX	Custon	n Length i	n Inches
	7/16 DIN		CONTACT			CENTE Humen	FEMALE UILDING 1 R INDUSTF ,523900,D0	, YONGFU SI Rial Park, N Dngguan, G	CIENCE AND TI Ianzha distri Iuangdong, (CHNOLOGY CT 5,
					- 1				E.	
9 H% % TO 7/16 DIN FEMALE					-					SIZE A 2233
REV. B FSCM NO. 53919 CAD FILE 122211 SCALE N/A SIZE A 2233				2.		SS OTHERWISE SPECIFIED PECIFICATIONS ARE SUB. ISIONS ARE IN INCHES. TH TOLERANCE IS ± 1.5% (JUI NUTICE AT	ANY TIME.