


Fire Rated 7/16 DIN Male to N Male Low PIM Cable 24 Inch Length Using SPF-250 Coax Using Times Microwave Parts

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	05/16/19	S.ELLIS



THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS		<p>ebeestock</p> <p>8TH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5.HUMEN,523900,DONGGUAN, GUANGDONG, CHINA</p> <p>WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com</p>		THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF EBEESTOCK CORPORATION. ALL RIGHTS RESERVED.					
<p>TOLERANCES:</p> <table border="0"> <tr> <td>.X±.2 [5.08]</td> <td>FRACTIONS ± 1/32</td> </tr> <tr> <td>.XX±.01 [.25]</td> <td>ANGLES ± 1°</td> </tr> <tr> <td>.XXX±.005 [.13]</td> <td></td> </tr> </table>				.X±.2 [5.08]	FRACTIONS ± 1/32	.XX±.01 [.25]	ANGLES ± 1°	.XXX±.005 [.13]	
.X±.2 [5.08]	FRACTIONS ± 1/32								
.XX±.01 [.25]	ANGLES ± 1°								
.XXX±.005 [.13]									
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.		SCALE N/A							
THIRD-ANGLE PROJECTION		SIZE	CAGE	DRAWN BY	PART NUMBER				
		A	53919	K.DANG	ET16419				
					REV A				