


# Fire Rated 7/16 DIN Male to 7/16 DIN Male Low PIM Cable 60 Inch Length Using SPF-500 Coax Using Times Microwave Parts

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	07/19/19	S.ELLIS



THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [ ] ARE MILLIMETERS <b>TOLERANCES:</b> .X±.2 [5.08]    FRACTIONS ± 1/32 .XX±.01 [ .25]    ANGLES ± 1° .XXX±.005 [ .13]		<p>                     8TH FLOOR, BUILDING 1,                      YONGFU SCIENCE AND TECHNOLOGY                      CENTER INDUSTRIAL PARK, NANZHA DISTRICT                      5, HUMEN, 523900, DONGGUAN, GUANGDONG, CHINA                      WEBSITE: <a href="http://www.ebeestock.com">www.ebeestock.com</a>                      EMAIL: <a href="mailto:sales@ebeestock.com">sales@ebeestock.com</a> </p>	THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF EBEESTOCK CORPORATION. ALL RIGHTS RESERVED.
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. THIRD-ANGLE PROJECTION			SHEET 1 OF 1 SCALE N/A
SIZE A	CAGE 53919	DRAWN BY K.DANG	PART NUMBER ET16539 REV A