## REVISIONS REV. DESCRIPTION DATE APPROVED А INITIAL RELEASE 1/14/2021 S.ELLIS 1.29 LENGTH MEASURED FROM CONTACT TO CONTACT 32.6 .315 [8.00] MAX. PANEL 2X HEAT SHRINK BOOT PIM LEVEL -zzzdBc S/N: XXXXXXXX (SEE NOTE 1) (SEE NOTE 2) CONTACT 7/16 DIN FEMALE BULKHEAD **7/16 DIN MALE** 1.00+.01 25.5 Ø 1.15<sup>+.01</sup> 29.3<sup>+0.1</sup> MOUNTING HOLE NOTES: UNLESS OTHERWISE SPECIFIED THIRD-ANGLE PROJECTION ebeestock LEADING DIMENSIONS ARE INCHES CABLES 84" AND UNDER HAVE 1 LABEL CENTERED. CABLES OVER 84" HAVE 2 DIMENSIONS IN [] ARE MILLIMETERS 1. Ð TOLERANCES: LABELS, ONE AT EACH END 12.0" FROM THE END OF THE CONNECTOR. THE INFORMATION AND DESIGN IN THIS DOCUMENT .X = ±.2 [5.08] FRACTIONS 8TH FLOOR, BUILDING 1, 2. 6" FROM CABLE END 1 PLACE FOR ALL LENGTHS OF CABLE. .XX = ±.02 [.51] ± 1/32 IS THE PROPERTY OF .XXX = ±.005 [ .13 ] ANGLES ± 1° YONGFU SCIENCE AND TECHNOLOGY EBEESTOCK CORPORATION CENTER INDUSTRIAL PARK, NANZHA DISTRICT ALL RIGHTS RESERVED CABLE LENGTH (L) TOLERANCES: 5, HUMEN, 523900, DONGGUAN, GUANGDONG, CHINA SHEET OF L ≤ 12 [305] = +1 [25] / -0 1 1 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 WEBSITE: www.ebeestock.com 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 EMAIL: sales@ebeestock.com SCALE N/A 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0 SIZE CAGE CODE DRAWN BY ITEM NO. REV ALL DIMENSIONS SHOWN 53919 **K.DANG**

А

ARE FOR REFERENCE ONLY.

ET16555

А

## 7/16 DIN Male to 7/16 DIN Female Bulkhead Cable 36 Inch Length Using 1/4 inch Super lexible Coax

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.