| COMPONENTS | IMPEDANCE | | | Standard Lengths | |
|----------------------|------------------|-----------------|---|---|---|
| MHV MALE MHV MALE | 50 OHM 50 OHM | | | -12 | 12" |
| RG62A/U | 93 OHM | | | -24 | 24" |
| | | | | -36 | 36" |
| | | | | -48 | 48" |
| | | | | -60 | 60" |
| | | | | -XXX | Custom Length in inches |
| .570ø | | LENGTH MEASUREI | | | MHV MALE |
| in the set | | | CEN" | ER INDUSTR En,523900, DO Websit Email: Des. | , YONGFU SCIENCE AND TECHNOLOGY IAL PARK, NANZHA DISTRICT 5,)NGGUAN, GUANGDONG, CHINA E: www.ebeestock.com sales@ebeestock.com COAXIAL & FIBER OPTICS CABLE ASSEMBLY, RG62A/U, MHV MALE TO MHV MALE |
| | | | REV. A FSCM NO. 53915 NOTES: 1. UNLESS OTHERWISE SPECIFI 2. ALL SPECIFICATIONS ARE SU 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.55 | ED ALL DIMEN BJECT TO CH | IANGE WITHOUT NOTICE AT ANY TIME. |