| COMPONENTS           | IMPEDANCE        |   | Standard Lengths  |  |  |   |                                    |     |
|----------------------|------------------|---|---|--|--|---|------------------------------------|-----|
| MHV MALE<br>MHV MALE | 50 OHM<br>50 OHM |   |   | -12  | 12"  |   |                                    |     |
| RG142B/U             | 50 OHM           |   |   | -24  | 24"  |   |                                    |     |
|                      |                  |   |   | -36  | 36"  |   |                                    |     |
|                      |                  |   |   | -48  | 48"  |   |                                    |     |
|                      |                  |   |   | -60  | 60"  |   |                                    |     |
|                      |                  |   |   | -XXX   | Custom   | n Length i  | n inch                             | es  |
| .570¢                |                  | LENGTH MEASURED<br>CONTACT TO CO              |   |  | MHV  |   |                                    |     |
| ek ek                | eestock          | RoHS  | ebeestock<br>ET25280  | NDUSTRI<br>23900,DO<br>WEBSITI<br>EMAIL:<br>DES. C | IAL PARK, NA<br>INGGUAN, GI<br>E: www.ebees<br>sales@ebeest<br>COAXI,<br>CABLE ASSEM<br>WHV MALE (LE | ANZHA DISTRI<br>UANGDONG, C<br>stock.com<br>tock.com<br>AL & FIBER (<br>IBLY, RG142B/U,<br>AD FREE) | CT 5,<br>HINA<br>OPTICS<br>MHV MAL | LET |
|                      |                  | 2002/95/EC<br>RoHS<br>Compliance<br>Certified | REV. A FSCM NO. 53919<br>NOTES:<br>1. UNLESS OTHERWISE SPECIFIED AL<br>2. ALL SPECIFICATIONS ARE SUBJEC<br>3. DIMENSIONS ARE IN INCHES.<br>4. LENGTH TOLERANCE IS ± 1.5% OR | LL DIMEN   | ANGE WITHOU  | UT NOTICE AT  | SIZE A                             | -   |