

Snap-On MMBX Plug to SMA Female Bulkhead Cable 12 Inch Lengt h Using ET38399 Coax



RF Cable Assemblies Technical Data Sheet

ET25977


Configuration

Connector 1: Snap-On MMBX Plug
 Connector 2: SMA Female Bulkhead

Cable Type: ET38399

Features

- Max. Operating Frequency of 3 GHz
- Snap-On mating
- Low Profile Right Angle Configurations
- SMA Bulkhead, N Bulkhead and TNC Bulkhead Between-Series Configurations



Applications

- General Purpose Test
- PCB Probing

- PCB Testing
- PCB-to-Panel

Description

Ebeestock's MMBX cable assemblies are part of our full line of RF components available for same-day shipping. These MMBX cable assemblies are designed to connect MMBX system components or test connections, delivering signal frequencies as high as 3 GHz. Our family of MMBX cables can also be used to connect from PCB to panel, offering between series MMBX options with SMA Bulkhead, TNC Bulkhead and N Bulkhead assembly configurations. If none of our standard options fit your application, you can specify your own custom MMBX cable assembly using Ebeestock's online Cable Creator.

Our MMBX cable assembly datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave cable assemblies allow designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right cable assemblies for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same day.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|-------------------------|---------|--------------|---------|--------------|
| Frequency Range | DC | | 3 | GHz |
| VSWR | | | 1.4:1 | |
| Return Loss | | -15.56 | | dB |
| Insertion Loss | | | 0.67 | dB |
| Velocity of Propagation | | 70 | | % |
| Capacitance | | 29.4 [96.46] | | pF/ft [pF/m] |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Snap-On MMBX Plug to SMA Female Bulkhead Cable 12 Inch Length Using ET38399 Coax ET25977

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Snap-On MMBX Plug to SMA Female Bulkhead Cable 12 Inch Lengt h Using ET38399 Coax



RF Cable Assemblies Technical Data Sheet

ET25977

Specifications by Frequency

| Description | F1 | F2 | F3 | F4 | F5 | Units |
|-----------------------|------|------|------|------|------|-------|
| Frequency | 0.1 | 0.25 | 0.5 | 1 | 3 | GHz |
| Insertion Loss (Max.) | 0.28 | 0.33 | 0.39 | 0.48 | 0.67 | dB |

Mechanical Specifications

Cable Assembly

Length* 12 in [304.8 mm]

Cable

Cable Type
Impedance
Inner Conductor Type

ET38399
50 Ohms
Stranded

Inner Conductor Material and Plating Copper Clad Steel, Silver

Dielectric Type
Number of Shields
2

Shield Layer 1
Silver Plated Copper Braid
Silver Plated Copper Braid

Jacket Material FEP, Tan

Jacket Diameter 0.114 in [2.9 mm]

Repeated Minimum Bend Radius 0.6 in [15.24 mm]

Connectors

| Connector 1 | Connector 2 SMA Female Bulkhead | |
|------------------------|---|--|
| MMBX Plug | | |
| 50 Ohms | 50 Ohms | |
| Snap-On | | |
| 100 | | |
| Beryllium Copper, Gold | Gold | |
| PTFE | | |
| Brass, Gold | | |
| Brass, Gold | Brass, Nickel | |
| | MMBX Plug 50 Ohms Snap-On 100 Beryllium Copper, Gold PTFE Brass, Gold | |

Mechanical Specification Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Snap-On MMBX Plug to SMA Female Bulkhead Cable 12 Inch Length Using ET38399 Coax ET25977

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

^{*}All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.



Snap-On MMBX Plug to SMA Female Bulkhead Cable 12 Inch Lengt h Using ET38399 Coax



RF Cable Assemblies Technical Data Sheet

ET25977

Environmental Specifications

Temperature

Operating Range

-55 to +155 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

How to Order

Example: ET25977 = 12 inches long cable

ET3C4051-100cm = 100 cm long cable

Snap-On MMBX Plug to SMA Female Bulkhead Cable 12 Inch Length Using ET38399 Coax from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Snap-On MMBX Plug to SMA Female Bulkhead Cable 12 Inch Length Using ET38399 Coax ET25977

URL: https://www.ebeestock.com/snap-on-mmbx-plug-to-sma-female-bulkhead-cable-4-inch-length-using-rg316-ds-coax-0025974

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. <a href="Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

