

Snap-On MMBX Plug Right Angle to SMA Male Right Angle Cable 12 Inch Length Using ET38399 Coax



RF Cable Assemblies Technical Data Sheet

ET26031

Configuration


Connector 1: Snap-On MMBX Plug Right Angle

• Connector 2: SMA Male Right Angle

Cable Type: ET38399

Features

- Max. Operating Frequency of 3 GHz
- Snap-On mating
- Low Profile Right Angle Configurations
- SMA Bulkhead, N Bulkhead and TNC Bulkhead Between-Series Configurations



Applications

- General Purpose Test
- PCB Probing

- PCB Testing
- PCB-to-Panel

Description

Ebeestock's MMBX cable assemblies are part of our full line of RF components available for same-day shipping. These MMBX cable assemblies are designed to connect MMBX system components or test connections, delivering signal frequencies as high as 3 GHz. Our family of MMBX cables can also be used to connect from PCB to panel, offering between series MMBX options with SMA Bulkhead, TNC Bulkhead and N Bulkhead assembly configurations. If none of our standard options fit your application, you can specify your own custom MMBX cable assembly using Ebeestock's online Cable Creator.

Our MMBX cable assembly datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave cable assemblies allow designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right cable assemblies for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.4:1	
Return Loss		-15.56		dB
Insertion Loss			0.67	dB
Velocity of Propagation		70		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Snap-On MMBX Plug Right Angle to SMA Male Right Angle Cable 12 Inch Length Using ET38399 Coax ET26031

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Snap-On MMBX Plug Right Angle to SMA Male Right Angle Cable

12 Inch Length Using ET38399 Coax



RF Cable Assemblies Technical Data Sheet

ET26031

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.1	0.25	0.5	1	3	GHz
Insertion Loss (Max.)	0.28	0.33	0.39	0.48	0.67	dB

Mechanical Specifications

Repeated Minimum Bend Radius

Cable Assembly

Length* 12 in [304.8 mm] Diameter 0.315 in [8 mm]

Cable

Cable Type
Impedance
Inner Conductor Type

ET38399
50 Ohms
Stranded

Inner Conductor Material and Plating Copper Clad Steel, Silver

Dielectric Type
Number of Shields
2

Shield Layer 1
Silver Plated Copper Braid
Silver Plated Copper Braid

Jacket Material FEP, Tan

Jacket Diameter 0.114 in [2.9 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Snap-On MMBX Plug Right Angle to SMA Male Right Angle Cable 12 Inch Length Using ET38399 Coax ET26031

0.6 in [15.24 mm]

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Snap-On MMBX Plug Right Angle to SMA Male Right Angle Cable 12 Inch Length Using ET38399 Coax



RF Cable Assemblies Technical Data Sheet

ET26031

Connectors

Description	Connector 1	Connector 2	
Type	MMBX Plug Right Angle	SMA Male Right Angle	
Specification		MIL-STD-348A	
Impedance	50 Ohms	50 Ohms	
Connection Method	Snap-On		
Mating Cycles	100		
Contact Material and Plating	Beryllium Copper, Gold	Brass, Gold	
Contact Plating Specification		50 μin minimum	
Dielectric Type	PTFE	PTFE	
Outer Conductor Material and Plating	Brass, Gold		
Body Material and Plating	Brass, Gold	Brass, Nickel	
Body Plating Specification		100 μin minimum	
Coupling Nut Material and Plating		Brass, Nickel	
Coupling Nut Plating Specification		100 μin minimum	
Hex Size		5/16 inch	
Torque		3 in-lbs [0.34 Nm]	

Mechanical Specification Notes:

Environmental Specifications

Temperature

Operating Range

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Snap-On MMBX Plug Right Angle to SMA Male Right Angle Cable 12 Inch Length Using ET38399 Coax ET26031

-55 to +155 deg C

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

www.ebeestock.com

^{*}All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.



Snap-On MMBX Plug Right Angle to SMA Male Right Angle Cable 12 Inch Length Using ET38399 Coax



RF Cable Assemblies Technical Data Sheet

ET26031

How to Order

Part Number Configuration:

ET3C4061 - xx uu

Unit of Measure:

cm = Centimeters

chlank> = Inches

Base Number

Example: ET26031 = 12 inches long cable

ET3C4061-100cm = 100 cm long cable

Snap-On MMBX Plug Right Angle to SMA Male Right Angle Cable 12 Inch Length Using ET38399 Coax from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Snap-On MMBX Plug Right Angle to SMA Male Right Angle Cable 12 Inch Length Using ET38399 Coax ET26031

URL: https://www.ebeestock.com/snap-on-mmbx-plug-right-angle-to-sma-male-right-angle-cable-4-in ch-length-using-rg316-ds-coax-0026028

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

