

MMCX Plug to SMA Male Right Angle Cable 50 cm Length Using E T-ET-RG178 Coax , LF Solder



RF Cable Assemblies Technical Data Sheet

ET26227

Configuration

• Connector 1: MMCX Plug

• Connector 2: SMA Male Right Angle

Cable Type: ET-RG178

Features

• Max Frequency 3 GHz

70% Phase Velocity

FEP Jacket

Applications

General Purpose

Laboratory Use

Description

Ebeestock's ET26227 MMCX plug to SMA male right angle 50 cm cable using ET-RG178 coax is part of our full line of RF components available for same-day shipping. Ebeestock's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Ebeestock MMCX to SMA cable assembly has a plug to male gender configuration with 50 ohm flexible ET-RG178 coax. The ET26227 MMCX plug to SMA male cable assembly operates to 3 GHz. The right angle SMA interface on the ET-RG178 cable allows for easier connections in tight spaces.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.45:1	
Velocity of Propagation		70		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]
Operating Voltage (AC)			170	Vrms

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.1	0.25	0.5	1	3	GHz
Insertion Loss (Max.)	0.53	0.61	0.75	1.03	1.6	dB

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MMCX Plug to SMA Male Right Angle Cable 50 cm Length Using ET-RG178 Coax, LF Solder ET26227

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



MMCX Plug to SMA Male Right Angle Cable 50 cm Length Using E T-ET-RG178 Coax , LF Solder



RF Cable Assemblies Technical Data Sheet

ET26227

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax used in this assembly. Insertion Loss is estimated as 0.1 dB for the MMCX connector and 0.2 dB for the SMA connector.

Mechanical Specifications

Cable Assembly

Length* 19.68 in [499.87 mm]

Diameter 0.315 in [8 mm]

Cable

Cable Type
Impedance
Inner Conductor Type
Inner Conductor Material and Plating

ET-RG178
50 Ohms
Stranded
Copper Clad Steel, Silver

Dielectric Type
PTF

Number of Shields 1

Shield Layer 1
Silver Plated Copper Braid

Jacket Material FEP, Tan

Jacket Diameter 0.072 in [1.83 mm]

Repeated Minimum Bend Radius 0.4 in [10.16 mm]

Connectors

Description	Connector 1	Connector 2
Type	MMCX Plug	SMA Male Right Angle
Specification	BS EN 122340	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30 μin minimum	50 μin minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Gold	Brass, Nickel
Body Plating Specification	3 µin minimum	100 μin minimum
Coupling Nut Material and Plating		Brass, Nickel
Coupling Nut Plating Specification		100 μin minimum
Hex Size		5/16 inch
Torque		3 in-lbs [0.34 Nm]

Environmental Specifications

Temperature

Operating Range

-55 to +155 deg C

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MMCX Plug to SMA Male Right Angle Cable 50 cm Length Using ET-RG178 Coax, LF Solder ET26227

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



MMCX Plug to SMA Male Right Angle Cable 50 cm Length Using E T-ET-RG178 Coax , LF Solder



RF Cable Assemblies Technical Data Sheet

ET26227


Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

How to Order

Part Number Configuration:



Example: ET36336LF-12 = 12 inches long cable

ET36336LF-100cm = 100 cm long cable

MMCX Plug to SMA Male Right Angle Cable 50 cm Length Using ET-RG178 Coax, LF Solder from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MMCX Plug to SMA Male Right Angle Cable 50 cm Length Using ET-RG178 Coax, LF Solder ET26227

URL: https://www.ebeestock.com/mmcx-plug-to-sma-male-right-angle-cable-12-inch-length-using-rg1 78-coax-lf-solder-0026222

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

