COMPONENTS	IMPEDANCE			Standard Lengths	
MMCX PLUG	50 OHM			-12	12"
SMA MALE RG188A/U	50 OHM 50 OHM			-24	24"
				-36	36"
				-48	48"
				-60	60"
				-XXX	
				-2000	Oustom Length in mones
	MMCX PLUG	CONTACT TO CO	NIACI	SMA MALE	.312 HEX
C C			CE NT	R INDUSTR N,523900, DO Websit	YONGFU SCIENCE AND TECHNOLOG IAL PARK, NANZHA DISTRICT 5, INGGUAN, GUANGDONG, CHINA E: www.ebeestock.com sales@ebeestock.com COAXIAL & FIBER OPTICS
			ET26357	DES.	CABLE ASSEMBLY, RG188A/U, MMCX PLUG TO SMA MALE

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.

CAD FILE 020608

SIZE A 147

SCALE N/A

REV. A FSCM NO. 53919

4. LENGTH TOLERANCE IS ± 1.5% OR ± 3/8", WHICHEVER IS GREATER.