COMPONENTS	IMPEDANCE) i	Standard Lengths		
N MALE	50 OHM				-12	12"	
N FEMALE BULKHEAD PE-SR047FL	50 OHM 50 OHM				-24		
FE-SRU4/FE	JU OFIN						
					-36	36"	
					-48	48"	
					-60	60"	
					-XXX	Custom Len	gth in inches
N MALE	CONT	.810ø		.625-24 UI	NEF-2A	HOUNTING HE	.640 —.546
STH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN,523900, DONG GUAN, GUANGDONG, CHINA WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com COAXIAL & FIBER OPTICS DES. CABLE ASSEMBLY, PE-SR047FL, N MALE TO							
				T26996 SCM NO. 53919	N	CABLE ASSEMBLY, PEI FEMALE BULKHEAD	
			NOTES: 1. UNLESS 2. ALL SPI 3. DIMENS	OTHERWISE SPECIFIED A ECIFICATIONS ARE SUBJECTIONS ARE IN INCHES. IN TOLERANCE IS ± 1.5% OR	CT TO CHA	ANGE WITHOUT NOT	L. ICE AT ANY TIME.