| 201120112112 | | | - | | |
|------------------------------|------------------|------------------------------|--|---------------------------------|---|
| COMPONENTS | IMPEDANCE | | | 1 | Standard Lengths |
| N MALE N MALE RIGHT ANGLE | 50 OHM 50 OHM | | | -12 | 12" |
| RG316/U | 50 OHM | | | -24 | 24" |
| | | | | -36 | 36" |
| | | | | -48 | 48" |
| | | | | -60 | 60" |
| | | | | -XXX | Custom Length in inches |
| | | | | | |
| .800¢ N MALE | estig | LENGTH MEASURED FROM CONTACT | | | 1.350 N MALE RIGHT ANGLE |
| e lo | | | CENTER CENTER | INDUSTRI 23900,DO Websiti | YONGFU SCIENCE AND TECHNOLOGY AL PARK, NANZHA DISTRICT 5, NGGUAN, GUANGDONG, CHINA E: www.ebeestock.com Sales@ebeestock.com COAXIAL & FIBER OPTICS |
| | | | ET27117 | | CABLE ASSEMBLY, RG316/U, N MALE TO N MALE RIGHT ANGLE |
| | | | REV. A FSCM NO. 53919 | CAD FILE | E 012808 SCALE N/A SIZE A 147 |
| | | | NOTES: 1. UNLESS OTHERWISE SPECIFIED A 2. ALL SPECIFICATIONS ARE SUBJE 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.5% OF | СТ ТО СН | ANGE WITHOUT NOTICE AT ANY TIME. |