COMPONENTS	IMPEDANCE		Standard Lengths
N MALE N FEMALE	50 OHM	-	12 12"
N FEMALE	50 OHM	[<u>.</u>	24 24"
		The state of the s	36 36"
			48 48"
			60 60"
		-	XXX Custom Length in inches
_	LENGTH MEASURED F		
	CONTACT TO CONT	ACT	
│			
.800ø			<i>l</i>
<u> </u>			
	N_	.625ø—	, T
N MALE	~C.	FEN	N L.625-24 UNEF-2A
	×O.		
	estock		
			· a
		**************************************	DING 1, YONGFU SCIENCE AND TECHNOLOGY
			DUSTRIAL PARK, NANZHA DISTRICT 5, 900, DONG GUAN, GUANGDONG, CHINA
			/EBSITE: www.ebeestock.com :MAIL: sales@ebeestock.com
		CDCCStOCK	COAXIAL & FIBER OPTICS
			DES. CABLE ASSEMBLY, N MALE TO N FEMALE
		ET27340	
		SIZE A FOCIVITYO. 33313	CAD FILE 081307 SCALE N/A 127
			L DIMENSIONS ARE NOMINAL. TO CHANGE WITHOUT NOTICE AT ANY TIME.
		DIMENSIONS ARE IN INCHES. LENGTH TOLERANCE IS ± 1.5% OR ±	3/8", WHICHEVER IS GREATER.