| COMPONENTS | IMPEDANCE | | | Standard Lengths | |
|---------------------|------------------|-------------------------------|---|------------------|--|
| 7/16 MALE N MALE | 50 OHM 50 OHM | | | -12 | 12" |
| RG400/U | 50 OHM | | | -24 | 24" |
| | | | | -36 | 36" |
| | | | | -48 | 48" |
| | | | | -60 | 60" |
| | | | | -XXX | Custom Length in inches |
| | | | | , - | |
| - | | LENGTH MEASURED CONTACT TO CO | | | - |
| 1.250 HEX | | | <u>, </u> | | .800ø |
| 7. M <i>J</i> | /16 ALE | weesto? | | | N MALE |
| | | eloe | 8TH FLOOF | TER INDUSTR | YONGFU SCIENCE AND TECHNOLOGY IAL PARK, NANZHA DISTRICT 5, Ingguan, Guangdong, China |
| | نی | | ebeestock | | E: www.ebeestock.com sales@ebeestock.com COAXIAL & FIBER OPTICS |
| | | | ET27394 | DES. | CABLE ASSEMBLY, RG400/U, 7/16 MALE TO N MALE |
| | | | REV. A FSCM NO. 53919 | CAD FIL | E 013008 SCALE N/A SIZE A 147 |
| | | | NOTES: 1. UNLESS OTHERWISE SPECIFI 2. ALL SPECIFICATIONS ARE SL 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.5 | BJECT TO CH | ANGE WITHOUT NOTICE AT ANY TIME. |