


| COMPONENTS | IMPEDANCE |
|---------------------------|-----------|
| REVERSE POLARITY TNC MALE | 50 OHM |
| STANDARD N MALE | 50 OHM |
| RG178B/U | 50 OHM |
| | |

| Standard Lengths | |
|------------------|-------------------------|
| -12 | 12" |
| -24 | 24" |
| -36 | 36" |
| -48 | 48" |
| -60 | 60" |
| -XXX | Custom Length in inches |
| | |



RoHS
Compliance
Certified

 8TH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN, 523900, DONGGUAN, GUANGDONG, CHINA

WEBSITE: www.ebeeestock.com
EMAIL: sales@ebeeestock.com
COAXIAL & FIBER OPTICS

| | | | | |
|-----------------------------|----------------|---|-----------|------------|
| DWG TITLE ET27573 | | DES. CABLE ASSEMBLY, RG178B/U, REVERSE POLARITY TNC MALE TO STANDARD N MALE (LEAD FREE) | | |
| REV. A | FSCM NO. 53919 | CAD FILE 020608 | SCALE N/A | SIZE A 147 |

- NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES.
 4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $\pm 3/8"$, WHICHEVER IS GREATER.