| COMPONENTS | IMPEDANCE | | | Standard Lengths | |
|------------------------------|------------------|----------------------------|---|---|--|
| N MALE N MALE RIGHT ANGLE | 50 OHM 50 OHM | | -12 | 12" | |
| RG213/U | 50 OHM | | -24 | 24" | |
| | | | -36 | 36" | |
| | | | -48 | 48" | |
| | | | -60 | 60" | |
| | | | -XXX | Custom Length in inches | |
| .800¢ N MALE | | IGTH MEASURED FROM_CONTACT | _ | N MALE RIGHT ANGLE | |
| | | | HUMEN,523900,DC | LIAL PARK, NANZHA DISTRICT 5, DNG GUAN, GUANGDONG, CHINA E: www.ebeestock.com coaxial & Fiber Optics | |
| | | | ET279' 1 | CABLE ASSEMBLY, RG213/U, N MALE TO N MALE RIGHT ANGLE | |
| | | | REV. A FSCM NO. 53919 CAD FINOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIME 2. ALL SPECIFICATIONS ARE SUBJECT TO CI 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.5% OR 3/8", WI | | |