



## RF Cable Assemblies Technical Data Sheet

ET29332

# Configuration

Connector 1: M39012/01-0503(N Male)
Connector 2: M39012/01-0503(N Male)

Cable: M17/128-ET-RG400

## Features

• Max Frequency 11 GHz

- 69.5% Phase Velocity
- Double Shielded
- Lot Traceability
- J-STD-Soldering
- Qualified (QPL) cable and connectors
- RF Test Plots
- Test Report
- In stock and ready to ship

## Applications

Hi-Rel

Avionics

SATCOM

• MIL-DTL-17 Requirements

• IFF

• ECM

## Description

Ebeestock's MIL-DTL-17 cable assemblies are part of our full line of reliable RF components available for same-day shipping. These commercial-off-the-shelf (COTS), military grade cable assemblies are designed and processed with high reliability in mind. MIL-PRF-39012 connectors and MIL-C-17 coaxial cable are assembled using J-STD soldering processes and WHMA-A-620 workmanship criteria. The combination of materials, processing and acceptance testing work together to create a dependable cable assembly for applications where performance over time is important or the cost of failure is high. Each finished MIL-DTL-17 cable assembly is traceable to its component lots and a test report is available for every lot produced.

Our MIL-DTL-17 cable assembly datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave cable assemblies allow designers to configure and customize their signal connections however they like. Whether the need is to provide reliable mil-spec connections or fielding dependable RF cable assemblies, Ebeestock has the right cable assemblies for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same day.

#### Referenced Specifications

IPC/WHMA-A-620 Requirements and Acceptance for Cable and Wire Harness Assemblies MIL-DTL-17 Cables, Radio Frequency, Flexible and Semirigid, General Specification for

MIL-STD-348 Radio Frequency Connector Interfaces for MIL-DTL-3643, MIL-DTL-3650, MIL-DTL-3655, MIL-

DTL-25516, MIL-PRF-31031, MIL-PRF-39012, MIL-PRF-49142, MIL-PRF...

MIL-PRF-39012 Connectors, Coaxial, Radio Frequency, General Specification for IPC J-STD-001 Requirements for Soldered Electrical and Electronic Assemblies

IPC J-STD-006

Requirements for Electronic Grade Solder Alloys and Fluxed and Non-Fluxed Solid Solders for

Electronic Soldering Applications

Marking of Electrical Insulating Materials

SAE AS23053 Insulation Sleeving, Electrical, Heat Shrinkable, General Specifications For

SAE AS22520 Crimping Tools, Wire Termination, General Specification For

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MIL-DTL-17 N Male to N Male Cable 48 Inch Length Using M17/128-ET-RG400 Coax ET29332

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

SAE AS5942





# RF Cable Assemblies Technical Data Sheet

ET29332

## Material Specifications

Component	Specification
Cable	M17/128-ET-RG400 in accordance with MIL-DTL-17
Connector 1	M39012/01-0503 in accordance with MIL-PRF-39012
Connector 2	M39012/01-0503 in accordance with MIL-PRF-39012
Heat Shrink 1	M23053/5-106-0 in accordance with SAE AS23053
Heat Shrink 2	M23053/5-106-0 in accordance with SAE AS23053
Solder	SN63 in accordance with J-STD-006

## Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		11	GHz
VSWR			1.6:1	
Velocity of Propagation		69.5		%
Capacitance		32 [104.99]		pF/ft [pF/m]
DC Resistance Inner Conductor		0.91 [2.99]		Ω/1000ft [Ω/Km]
Dielectric Withstanding Voltage (AC)			1,500	Vrms

## Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.4	1	3	10	11	GHz
Insertion Loss (Max.)	0.62	0.88	1.72	3.32	3.52	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax cable used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB for each connector.

### Mechanical Specifications

#### Cable Assembly

Description	Minimum	Typical	Maximum	Units
Length*	48 [121.92]	48 [121.92]	49 [124.46]	in [cm]
Cable Outer Diameter	0.19	0.195	0.2	in
Weight			0.41 [185.97]	lbs [g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MIL-DTL-17 N Male to N Male Cable 48 Inch Length Using M17/128-ET-RG400 Coax ET29332





# RF Cable Assemblies Technical Data Sheet

ET29332

\*Length Tolerances: +0.5, -0 inches for Length ≤ 1 foot; +1, -0 inches for Length >1 to 5 feet; +2, -0 inches for Length >5 to 10 feet; +3, -0 inches for Length >10 to 25 feet and +2%, -0 inches for Length >25 feet.

#### Cable Characteristics

Description	Specification	
Cable Type	M17/128-ET-RG400	
Impedance	50 Ohms	
Inner Conductor Type	Stranded	
Inner Conductor Material and Plating	Copper Clad Steel, Silver	
Dielectric Type	PTFE	
Number of Shields	2	
Shield Layer 1	Silver Clad Copper	
Shield Layer 2	Silver Clad Copper	
Outer Conductor Diameter	0.171 in [4.34 mm]	

#### **Connector Characteristics**

Description	Connector 1	Connector 2
Туре	N Male	N Male
Specification	MIL-PRF-39012	MIL-PRF-39012
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	MIL-G-45204	MIL-G-45204
Dielectric Type	Teflon	Teflon
Body Material and Plating	Brass, Silver	Brass, Silver
Body Plating Specification	QQ-S-365	QQ-S-365
Seal Gasket Material	Silicone Rubber	Silicone Rubber
Contact Gage Specification	0.210 in min	0.210 in min

Mechanical Specification Notes:

## **Environmental Specifications**

Description	Specification	
Temperature Operating Range	-55 to +165 deg C	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MIL-DTL-17 N Male to N Male Cable 48 Inch Length Using M17/128-ET-RG400 Coax ET29332

www.ebeestock.com





# RF Cable Assemblies Technical Data Sheet

ET29332

Compliance Certifications (see product page for current document)

## Process Specifications

Process	Specification
Soldering	in accordance with J-STD-001, class3
Crimping	dies in accordance with SAE AS22520
Marking	shall meet the adherence requirements of SAE AS5942
Workmanship	shall be in accordance with IPC/WHMA-A-620, class 3

## Tests and Inspections

Description	Sampling	
Connector Gaging (pin and insulator position)	100%	
Insertion Loss	100%	
VSWR	100%	
Dielectric Withstanding Voltage (DWV)	100%	
Visual -workmanship, configuration and marking	100%	
Length	C=0, 1.5AQL	
Mass	C=0, 1.5AQL	

## Plotted and Other Data

Notes:

Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MIL-DTL-17 N Male to N Male Cable 48 Inch Length Using M17/128-ET-RG400 Coax ET29332





# RF Cable Assemblies Technical Data Sheet

ET29332

#### How to Order

Part Number Configuration:

ET3M0064
- xx uu

Unit of Measure:

cm = Centimeters

<br/>
<br/>
<br/>
<br/>
chlank> = Inches

Base Number


Example: ET3M0064-12 = 12 inches long cable ET3M0064-100cm = 100 cm long cable


MIL-DTL-17 N Male to N Male Cable 48 Inch Length Using M17/128-ET-RG400 Coax from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MIL-DTL-17 N Male to N Male Cable 48 Inch Length Using M17/128-ET-RG400 Coax ET3M0064- 48

**URL:** https://www.ebeestock.com/mil-dtl-17-n-male-to-n-male-cable-12-inch-length-using-m17-128-r g400-coax-0029327

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.





Ebeestock.com
8th Floor, Building 1, Yongfu Science

NS IN INCHES

and Technology Center Industrial Park,

Nanzha District 5, Humen,523900, Dongguan, Guangdong,

Webstie: www.ebeestock.com Email: sales@ebeestock.c