


| COMPONENTS | IMPEDANCE |
|------------|-----------|
| SMP FEMALE | 50 OHM    |
| SMP FEMALE | 50 OHM    |
|            |           |
|            |           |

| Standard Lengths |                         |
|------------------|-------------------------|
| -12              | 12"                     |
| -24              | 24"                     |
| -36              | 36"                     |
| -48              | 48"                     |
| -60              | 60"                     |
| -XXX             | Custom Length in inches |
|                  |                         |




**8TH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN, 523900, DONGGUAN, GUANGDONG, CHINA**  
 WEBSITE: [www.ebeestock.com](http://www.ebeestock.com)  
 EMAIL: [sales@ebeestock.com](mailto:sales@ebeestock.com)



RoHS  
Compliance  
Certified

|                |                       |   |           |            |
|----------------|-----------------------|---|-----------|------------|
| <b>ET32209</b> |                       | DES. CABLE ASSEMBLY, SMP FEMALE TO SMP FEMALE (LEAD FREE) |           |            |
| REV. A         | <b>FSCM NO. 53919</b> | CAD FILE 020808   | SCALE N/A | SIZE A 147 |

- NOTES:**
- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
  - ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
  - DIMENSIONS ARE IN INCHES.
  - LENGTH TOLERANCE IS  $\pm 1.5\%$  OR  $\pm 3/8"$ , WHICHEVER IS GREATER.