



RF Cable Assemblies Technical Data Sheet

ET32504

Configuration

Connector 1: SMA Female Bulkhead
 Connector 2: SMP Female Right Angle

Cable Type: ET-RG178

Features

- Max Frequency 3 GHz
- 70% Phase Velocity
- FEP Jacket

Applications

General Purpose

Laboratory Use

Description

Ebeestock's ET32504 SMA female bulkhead to SMP female right angle 48 inch cable using ET-RG178 coax is part of our full line of RF components available for same-day shipping. Ebeestock's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Ebeestock SMA to SMP cable assembly has a female to female gender configuration with 50 ohm flexible ET-RG178 coax. The ET32504 SMA female to SMP female cable assembly operates to 3 GHz. The right angle SMP interface on the ET-RG178 cable allows for easier connections in tight spaces. Our RF cable assembly with SMA bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.4:1	
Velocity of Propagation		70		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Bulkhead to SMP Female Right Angle Cable 48 Inch Length Using ET-RG178 Coax with HeatShrink ET32504

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.





RF Cable Assemblies Technical Data Sheet

ET32504

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.25	0.5	1	2.5	3	GHz
Insertion Loss (Max.)	1.14	1.52	2.08	3.1	3.44	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax used in this assembly. The Insertion Loss includes an estimated loss of 0.3dB of connector loss.

Mechanical Specifications

Cable Assembly

Length* 48 in [121.92 cm] 0.433 in [11 mm] Diameter

Cable

Cable Type ET-RG178 Impedance 50 Ohms Stranded Inner Conductor Type

Inner Conductor Material and Plating Copper Clad Steel, Silver

Dielectric Type PTFE Number of Shields

Silver Plated Copper Braid Shield Layer 1 Jacket Material FEP, Tan

0.072 in [1.83 mm] Jacket Diameter

Repeated Minimum Bend Radius 0.4 in [10.16 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Bulkhead to SMP Female Right Angle Cable 48 Inch Length Using ET-RG178 Coax with HeatShrink ET32504

www.ebeestock.com

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen, 523900, Dongguan, Guangdong, China.





RF Cable Assemblies Technical Data Sheet

ET32504

Connectors

Description	Connector 1	Connector 2	
Type	SMA Female Bulkhead	SMP Female Right Angle	
Specification		MIL-STD-348A	
Impedance	50 Ohms	50 Ohms	
Mating Cycles	500		
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold	
Contact Plating Specification		MIL-DTL-45204	
Dielectric Type	PTFE	PTFE	
Outer Conductor Material and Plating	Brass, Gold	Beryllium Copper, Gold	
Outer Conductor Plating Specification		MIL-DTL-45204	
Body Material and Plating	Brass, Gold	Brass, Gold	
Body Plating Specification		MIL-DTL-45204	
Coupling Nut Material and Plating	Brass, Gold		

Mechanical Specification Notes:

Environmental Specifications

Temperature

Operating Range

-55 to +155 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Bulkhead to SMP Female Right Angle Cable 48 Inch Length Using ET-RG178 Coax with HeatShrink ET32504

www.ebeestock.com

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

^{*}All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.





RF Cable Assemblies Technical Data Sheet

ET32504

How to Order

Part Number Configuration:

ET3W05697/HS - xx uu

——Unit of Measure:

cm = Centimeters

Length
Base Number

Example: ET3W05697/HS-12 = 12 inches long cable

ET3W05697/HS-100cm = 100 cm long cable

SMA Female Bulkhead to SMP Female Right Angle Cable 48 Inch Length Using ET-RG178 Coax with HeatShrink from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Bulkhead to SMP Female Right Angle Cable 48 Inch Length Using ET-RG178 Coax with HeatShrink ET32504

URL: https://www.ebeestock.com/sma-female-bulkhead-to-smp-female-right-angle-cable-12-inch-leng th-using-rg178-coax-with-heatshrink-0032501

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

