COMPONENTS	OMPONENTS IMPEDANCE Standa		
SSMA MALE	50 OHM	Otandard Lengths	
SMA MALE	50 OHM	-12 12"	
RG316/U	50 OHM	-24 24"	
		-36 36"	Į
		-48 48"	
		-60 60"	1
		-XXX Custom Len	gth in inches
	SMA	LENGTH MEASURED FROM CONTACT TO CONTACT .312 HE: SMA MALE STH FLOOR, BUILDING 1, YONGFU SCIENCE AND	D TECHNOLO GY
		CENTER INDUSTRIAL PARK, NANZHA DIS Humen,523900, do ng guan, g uangdo n	
		ebeestock WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com	
		ESTABLISHED 2003 COAXIAL & F	IBER OPTICS
		ET32732 DES. CABLE ASSEMBLY, RG TO SMA MALE	316/U, SSMA MALE
		REV. A FSCM NO. 53919 CAD FILE 021108 SCALE	N/A SIZE A 127
		NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTI 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.5% OR ±3/8", WHICHEVER IS GREATE	ICE AT ANY TIME.