| MA MALE 50 OHM A MALE 50 OHM -12 12"   | COMPONENTS | IMPEDANCE |                      |                         |   |           |            |                  | 40        |
|--|------------|-----------|----------------------|-------------------------|---|-----------|------------|------------------|-----------|
| A MALE   50 OHM   -12   12"   -24   24"   -36   36"   -48   48"   -60   60"   -XXX   Custom Length in inches   | SMA MALE   |           |                      |                         |   | _         | 1          | dard Leng        | ths       |
| 24   24"   -36   36"   -48   48"   -60   60"   -XXX   Custom Length in inches   Contact To Contact   -312   HEX   -350   HEX   -36   36"   -48   48"   -36   36"   -48   48"   -36   36"   -48   48"   -36   36"   -36"   - | MA MALE    | 50 OHM    |                      |                         |   | -12       | 12"        |                  |           |
| LENGTH MEASURED FROM CONTACT TO CONTACT  LENGTH MEASURED FROM CONTACT TO CONTACT  312 HEX  SSMA  | G316/U     | 50 OHM    |                      |                         |   | -24       | 24"        |                  |           |
| LENGTH MEASURED FROM CONTACT TO CONTACT  .250 HEX  SSMA  .250 HEX  |            |           |                      |                         |   | -36       | 36"        |                  |           |
| LENGTH MEASURED FROM CONTACT TO CONTACT  .250 HEX SSMA  Custom Length in inche   |            |           |                      |                         |   | -48       | 48"        |                  |           |
| LENGTH MEASURED FROM CONTACT TO CONTACT  .250 HEX  SSMA  SMA   |            |           |                      |                         |   | -60       | 60"        |                  |           |
| CONTACT TO CONTACT  .250 HEX  SSMA  SMA  |            |           |                      |                         |   | -XXX      | Custor     | n Length i       | n inche   |
| MALE MALE  |            | <u></u>   | LENGTH ME<br>CONTACT | EASURED FROM TO CONTACT | <u>ه</u>  | SMA       | <u></u>    | 2 HEX            |           |
|  |            |           |                      |                         |   | DES. C    | CABLE ASSE | MBLY, RG316/U, S | SSMA MALI |
| DWG TITLE  DES. CABLE ASSEMBLY, RG316/U, SSMA MALI TO SMA MALE   |            |           |                      | REV. A                  | FSCM NO. 53919  | CAD FILE  | 021108     | SCALE N/A        | SIZE A    |
| ET32737  CABLE ASSEMBLY, RG316/U, SSMA MALI TO SMA MALE  |            |           |                      | 2. ALL<br>3. DIMI       | ESS OTHERWISE SPECIFIED A<br>SPECIFICATIONS ARE SUBJE<br>ENSIONS ARE IN INCHES.<br>GTH TOLERANCE IS ± 1.5% OF | CT TO CHA | ANGE WITHO | OUT NOTICE AT    | ANY TIME. |