COMPONENTS	IMPEDANCE				4:4			
SSMA MALE	50 OHM				_	Stan	dard Leng	gths
SMA MALE	50 OHM				-12	12"		
RG316/U	50 OHM				-24	24"		
					-36	36"		
					-48	48"		
					-60	60"		
					-XXX	Custor	n Length i	n inches
.250 HEX	SMA IALE		EASURED FROM TO CONTACT	٩	SMA		2 HEX	
		- in		HUMEN,5	INDUSTRV 23900, do i	AL PARK, NA NGGUAN, GU	NZHA DISTRICT Angdong, Chi	5,
			6	ebeestock		: www.ebeest ales@ebeest		
				ESTABLISHED 2003		COAX	IAL & FIBER	OPTICS
			DWG T	T32746	DES.	CABLE ASSEI TO SMA MALE	MBLY, RG316/U, (LEAD FREE)	SSMA MALE
			REV. A	FSCM NO. 53919	CAD FIL	E 021108	SCALE N/A	SIZE A 12
			2. ALL 3. DIM	: LESS OTHERWISE SPECIFIED A SPECIFICATIONS ARE SUBJE ENSIONS ARE IN INCHES. GTH TOLERANCE IS ± 1.5% OF	CT TO CH	ANGE WITHO	OUT NOTICE AT	ANY TIME.