COMPONENTS	IMPEDANCE			7	4: 4			
SSMA MALE	50 OHM					T	dard Leng	yths
MA MALE	50 OHM				<u>-12</u>	12"		
RG316/U	50 OHM				-24	24"		
	1				-36	36"		
					-48	48"		
					-60	60"		
					-XXX	Custor	n Length i	n inches
				į,				
	_		MEASURED FROM	\$		_		
	-ate	CONTAC	CT TO CONTACT					
				NL.			1	
<u> </u>					_	<u>بر</u> ا		
						31	2 HEX	
<b>↑</b>				~		<del></del>	<u> </u>	
.250 HEX─			03					
	SSMA MALE		00		SMA Mali			
			<b>100</b>					
					<u> </u>			
		- Sta			INDUSTRU	AL PARK, NA	NZHA DISTRICT	5,
					-	: www.ebeest	ANGDONG, CHII ock.com	••
			,	ebeestock	EMAIL: s	ales@ebeesto		
			Divis-	ESTABLISHED 2003	DEC		IAL & FIBER	
			DWG T	T32747	DES.	CABLE ASSEI TO SMA MALE	MBLY, RG316/U, S E (LEAD FREE)	SSMA MALE
			REV. A	FSCM NO. 53919	CAD FILI	E 021108	SCALE N/A	SIZE A 127
			2. ALI	LESS OTHERWISE SPECIFIED A L SPECIFICATIONS ARE SUBJEC				ANY TIME.
				ENSIONS ARE IN INCHES. IGTH TOLERANCE IS ± 1.5% OR	± 3/8", WI	HICHEVER IS	GREATER.	