| COMPONENTS | IMPEDANCE | Standard Lengths |
|---------------|--------------------|--|
| TNC MALE | 75 OHM | |
| TNC MALE | 75 OHM | -12 12" |
| RG59B/U-BLACK | 75 OHM | -24 24" |
| ; ; | | -36 36" |
| | | -48 48" |
| | | -60 60" |
| | | -XXX Custom Length in inches |
| | | |
| | - | LENGTH MEASURED FROMCONTACT TO CONTACT |
| .590ø | | |
| .030, | 75 OHM TNC MALE | 75 OHM TNC MALE |
| | | STH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN,523900, DO NG GUAN, GUANGDO NG, CHINA WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com EMAIL: sales@ebeestock.com TOAXIAL & FIBER OPTICS DES. CABLE ASSEMBLY, RG598/U-BLACK, 75 OHM TNC MALE TO 75 OHM TNC MALE REV. A FSCM NO. 53919 CAD FILE 020608 SCALE N/A SIZE A 147 NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. |
| | | ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. DIMENSIONS ARE IN INCHES. LENGTH TOLERANCE IS ± 1.5% OR ± 3/8", WHICHEVER IS GREATER. |