| COMPONENTS | IMPEDANCE | | | | Standard Lengths | | | | |
|------------|------------------|-----------------------|----------------------------|---|------------------|-----------------------------|---------------------------------|-----------|------|
| INC MALE | 50 OHM 50 OHM | | | | -12 | 12" | | | |
| PE-SR047FL | 50 OHM | | | | -24 | 24" | | | |
| | | | | | -36 | 36" | | | |
| | | | | | -48 | 48" | | | |
| | | | | | -60 | 60" | | | |
| | | | | | -XXX | Custor | n Length i | n inch | ies |
| .590ø | | LENGTH MEA CONTACT | ASURED FROM_ TO CONTACT | | | |] | HNOLOG | Y |
| | | | | CENTEI CENTEI | R INDUSTR | IAL PARK, N | ANZHA DISTRIC Uangdong, Ch | T 5, | |
| | | | | ebeestock | | E: www.ebee: sales@ebees | | | |
| | | | | ESTABLISHED 2003 | 65. | COAX | IAL & FIBER | OPTICS | |
| | | | DWG | ITTLE E T 33 1 43 | DES. C | CABLE ASSEI | MBLY, PE-SR047 E (LEAD FREE) | FL, TNC M | IALE |
| | | | REV. A | | CAD FILE | E 013008 | SCALE N/A | SIZE A | 14 |
| | | | 2. AL 3. DIM | S: LLESS OTHERWISE SPECIFIED A L SPECIFICATIONS ARE SUBJE MENSIONS ARE IN INCHES. NGTH TOLERANCE IS ± 1.5% OR | CT TO CHA | ANGE WITHO | OUT NOTICE AT | ANY TIM | E. |